

**Product Sheet** 




ARES s.r.l - Socio Unico

v.le dell'Artigianato n.24 - 20881 Bernareggio - MB (Italy) www.aresill.net - flos.outdoor@flos.com

## Emma Ø150

Luminaire for installation on wall - surface mounted. Configuration: die-cast aluminium fixing base and frames, EN AB-47100 alloy (low copper content), extruded aluminium body. Glass dilffuser: transparent. Double layer coating for high resistance to corrosion: the aluminium components are painted with a double coat using powders that are compliant with QUALICOAT standards: a first layer of epoxy powder (with excellent chemical and mechanical resistance) and a second finishing layer of polyester powder (resistant to UV rays and atmospheric agents). The entire painting process of the aluminium fitting starts from components that have been sandblasted in advance to make the surface more porous and increase the adherence of the paint. Ares effects alkaline and acid washing to clean the surfaces completely, then rinses with demineralised water to remove any residue particles, subsequently a chemical conversion treatment is done to protect against rusting. Protection rating: IP65. In compliance with EN 60598-1 standards. Class of insulation: I. Installation: wiring through two cable holders (8mm<0-12mm cables). Outdoor use requires suitable flexible cables assuring the watertightness of the cable holder. A quick clamp placed in the wiring unit allows an easy connection and disconnection for installation or maintenance.

## Emma 150 / Unidirectional



### **Product Code Details**

1189821

Light Source




TC-TEL 26W GX24 q-3 Electronic ballast



# IP65 ♥ ⊕ C€

#### Available Colors for this Version



#### Warnings

#### Wall



Wall fitting



The fitting is equipped with 2 cable input.

Protection against impact. IK 07 - 02,00 joule

## Light Flux, Placement





This product has no accessories