

Product Sheet




ARES s.r.l - Socio Unico v.le dell'Artigianato n.24 - 20881 Bernareggio - MB (Italy) www.aresill.net - flos.outdoor@flos.com

Franco


Luminaire for installation on wall or on pole. Configuration: die-cast aluminium structure, EN AB-47100 alloy (low copper content) and pure aluminium reflector. Glass diffuser: extra-clear. Graduated stainless steel fixing plate for a precise adjustment. Double layer coating for high resistance to corrosion: the aluminium components are painted with a double coat using powders which are compliant with QUALICOAT standards: a first layer of epoxy powder (with excellent chemical and mechanical resistance) and a second finishing layer of polyester powder (resistant to UV rays and atmospheric agents). The entire painting process of the aluminium fitting starts from components which have been sand-blasted in advance to make the surface more porous and increase the adherence of the paint. Ares effects alkaline and acid washing to clean the surfaces completely, then rinses with demineralised water to remove any residue particles, subsequently a chemical conversion treatment is done to protect against rusting. Protection rating: IP65. In compliance with EN60598-1 standards. Class of insulation: I. Installation: wiring through a M20x1,5 metal cable gland (7mm<ø<13mm cables). Outdoor use requires suitable flexible cables assuring the watertightness of the cable gland.

Franco / Adjustable - Symmetric Optic



IP65 ♥ ⊕ C€

Available Colors for this Version



Warnings

Projector



Wall fitting



Floor installation



The fitting is equipped with 1 cable input



Protection against impact. IK 07 - 02,00 joule

Pole Top



Installation on pole



The fitting is equipped with 1 cable input



Protection against impact. IK 07 - 02,00 joule

Light Flux, Placement









Product Code Details

962913

Light Source



HIT-DE 70W RX7S





Code: 78 Single bracket 180 mm for pole Ø 102 mm (codes: 4140, 4145, 4150, 4155)



Code: 90 Double braket 180 mm Proper to pole ø 102 mm, code: 4140, 4145, 4150, 4155



Code: 79 Single bracket 500 mm for pole Ø 102 mm (codes: 4140, 4145, 4150, 4155)



Code: 89 Double braket 500 mm Proper to pole ø 102 mm, code: 4140, 4145, 4150, 4155



Code: 93 Single bracket 180 mm for pole Ø 60 mm (codes: 1005, 1009, 1105, 1109)



Code: 95 Double braket 180 mm Proper to pole ø 60 mm, code: 1005, 1009, 1105, 1109



Code: 94 Single bracket 500 mm for pole Ø 60 mm (codes: 1005, 1009, 1105, 1109)



Code: 96 Double braket 500 mm Proper to pole Ø 60 mm, code: 1005, 1009, 1105, 1109



Code: 112 Single bracket 180 mm for pole Ø 76 mm (codes: 248, 249, 250, 251)



Code: 114 Double braket 180 mm for pole Ø 76 mm



Code: 113 Single bracket 500 mm for pole Ø 76 mm (codes: 248, 249, 250, 251)



Code: 115 Double braket 500 mm for pole Ø 76 mm



Code: 116 Base plate and pole fixing bolts 230 x 230 x H 200 mm



Code: 248
Pole with Base and Access Door
With Terminal Block 4x1,5-16mmq
ø76 mm
H 3500 mm
.6 grey
.3 anthracite



Code: 249
Pole with Base and Access Door
With Terminal Block 4x1,5-16mmq
Ø76 mm
H 4500 mm
.6 grey
.3 anthracite



Code: 250 In-Ground Pole (+500 mm Root) With Access Door With Terminal Block 4x1,5-16mmq Ø76 mm H 3500 mm (+500 mm) .6 grey .3 anthracite



Code: 251
In-Ground Pole (+500 mm Root)
With Access Door With Terminal Block 4x1,516mmq
Ø76 mm
H 4500 mm (+500 mm)
.6 grey
.3 anthracite



Code: 4140
Pole with Base and Access Door
With Terminal Block 4x1,5-16mmq
ø102mm
H 4000mm
.6 grey
.3 anthracite



Code: 4145
In-Ground Pole (+500 mm Root)
With Access Door With Terminal Block 4x1,516mmq
Ø102mm
H 4000mm (+500 mm)
.6 grey
.3 anthracite



Code: 4150
Pole with Base and Access Door
With Terminal Block 4x1,5-16mmq
ø102mm
H 5000mm
.6 grey
.3 anthracite

16n Ø10 H 5

With Access Door With Terminal Block 4x1,5-16mmq ø102mm H 5000mm (+500 mm) .6 grey .3 anthracite