842800


Product Sheet

Jackie

Luminaire for installation on wall - surface mounted. Configuration: die-cast aluminium structure, EN AB-47100 alloy (low copper content). Glass diffuser: transparent. Double layer coating for high resistance to corrosion: the aluminium components are painted with a double coat using powders that are compliant with QUALICOAT standards: a first layer of epoxy powder (with excellent chemical and mechanical resistance) and a second finishing layer of polyester powder (resistant to UV rays and atmospheric agents). The entire painting process of the aluminium fitting starts from components that have been sandblasted in advance to make the surface more porous and increase the adherence of the paint. Ares effects alkaline and acid washing to clean the surfaces completely, then rinses with demineralised water to remove any residue particles, subsequently a chemical conversion treatment is done to protect against rusting. Protection rating: IP54. In compliance with EN 60598-1 standards. Class of insulation: mains 1; low voltage: III. Installation: wiring through a rubber cable holder (5mm<Ø~10mm cables). Outdoor use requires suitable flexible cables assuring the watertightness of the cable holder.

Jackie / Transparent Glass





Product Code Details



Light Source



PAR 16 35W/230V GZ10






ARES s.r.l - Socio Unico v.le dell'Artigianato n.24 - 20881 Bernareggio - MB (Italy) www.aresill.net - flos.outdoor@flos.com

IP54 ♥⊕C€

Available Colors for this Version



Warnings



Remote device required for 12V versions

Wall fitting



The fitting is equipped with 1 cable input

Protectio IK 08 - 05

Protection against impact. IK 08 - 05,00 joule

Light Flux, Placement





This product has no accessories