
12316254


Product Sheet

Leo

Luminaire for installation on wall and on post - surface mounted. Configuration: die-cast aluminium structure, EN AB-47100 alloy (low copper content). Diffuser: lens or transparent or sandblasted glass fixed to the structure through a robotic gluing system. Double layer coating for high resistance to corrosion: the aluminium components are painted with a double coat using powders that are compliant with QUALICOAT standards: a first layer of epoxy powder (with excellent chemical and mechanical resistance) and a second finishing layer of polyester powder (resistant to UV rays and atmospheric agents). The entire painting process of the aluminium fitting starts from components that have been sandblasted in advance to make the surface more porous and increase the adherence of the paint. Ares effects alkaline and acid washing to clean the surfaces completely, then rinses with demineralised water to remove any residue particles, subsequently a chemical compliance with EN 60598-1 standards Class of insulation: I Installation: wiring through two cable holders (8mm<Ø-13mm cables). Outdoor use requires suitable flexible cables assuring the watertightness of the cable holder. For watertightness to be assured the use of a multicore cable is mandatory, the use of single unipolar cables is not allowed.

Leo120 / Bidirectional - Combined: Narrow Beam 4° (Convex Lens) + Wide Beam 75°





Product Code Details



Light Source



HIT-TC-CE 20W GU6,5 Electronic ballast






ARES s.r.l - Socio Unico v.le dell'Artigianato n.24 - 20881 Bernareggio - MB (Italy) www.aresill.net - flos.outdoor@flos.com

IP65 🗑 🕀 🤆

Available Colors for this Version



Warnings





The fitting is equipped with 2 cable input.



Protection against impact. IK 05 - 0,70 joule

Wall fitting

Light Flux, Placement



This product has no accessories