

10514400

Product Sheet


ares
THE OUTDOOR BY FLOS

ARES s.r.l - Socio Unico
v.le dell'Artigianato n.24 - 20881 Bernareggio - MB (Italy)
www.aresill.net - flos.outdoor@flos.com

Martina


Adjustable spotlight. Configuration: turned and anodized (raw or painted) aluminium structure with stainless steel adjustable bracket. Glass diffuser: transparent or sandblasted with silkscreen border, fixed through a robotic gluing system. Double layer coating for high resistance to corrosion: the aluminium components are painted with a double coat using powders which are compliant with QUALICOAT standards: a first layer of epoxy powder (with excellent chemical and mechanical resistance) and a second finishing layer of polyester powder (resistant to UV rays and atmospheric agents). The entire painting process of the aluminium fitting starts from components which have been sand-blasted in advance to make the surface more porous and increase the adherence of the paint. Ares effects alkaline and acid washing to clean the surfaces completely, then rinses with demineralised water to remove any residue particles, subsequently a chemical conversion treatment is done to protect against rusting. Protection rating: IP67. In compliance with EN60598-1 standards. Class of insulation: III. Installation: the luminaire is equipped with 2000mm cable. Martina 24V and Maxi Martina 24V are equipped with a dc/dc highly efficient resin-coated converter that removes electromagnetic interference and protects against polarity reversal and sudden voltage peak. Parallel wiring required. Mini Martina, Martina RGB and Maxi Martina RGB requires connection in series. We recommend the use of a connection system with a protection degree greater than or equal to the protection degree of the luminaire.

MiniMartina Power LED / Transparent Glass -
Adjustable - Medium Beam 30°



IP67

Available Colors for this Version



8. anodized aluminium

Warnings

Projector



Ceiling lamp.



Wall lamp.



Floor installation



Pre-wired with approx 2000mm of cable.



Remote device required



Protection against impact.
IK 05 - 0,70 joule MiniMartina
IK 07 - 2,00 joule
Martina/MaxiMartina

Light Flux, Placement



Product Code Details

10514400

Light Source



WARM WHITE 3000K POWER LED 1x1÷2W/350mA

Total power 1,1W@350mA - 1,6W@500mA

lm LED 120@350mA ÷ lm OUTPUT 101@350mA

lm LED 180@500mA ÷ lm OUTPUT 119@500mA

CRI>80

Remote electronic power supply to be ordered





Code: 136
Ground spike
H 200 mm



Code: 150
Supported n. of lamps: 6
Power supply dual function
Vout 24Vdc: 8W/100÷240V
Iout 350mA: 6X1W/100÷240V
IP20 CLASS II SELV EQ.



Code: 106
Supported n. of lamps: 6
Power supply dual function
Vout 24Vdc: 8W/100÷240V
Iout 350mA: 6X1W/100÷240V - IP65 CLASS II SELV EQ.



Code: 68
Supported n. of lamps: 10
Power supply
10x1W/100÷265V - Iout 350mA
(7x1W@110V) IP40 CLASS II SELV EQ.



Code: 129
Supported n. of lamps: 16
Power supply
16x1W/110÷240V - Iout 350mA
(12x1W@110V) IP20 CLASS II SELV EQ.



Code: 184
Supported n. of lamps: 16
Power supply
16X1W/110÷240V - Iout 350mA (12X1W@110V)
IP67 CLASS II SELV.



Code: 135
Supported n. of lamps: 12
Power supply
13x2W/110÷240V-Iout 500mA
(7x2W@110V) IP20 CLASS II SELV EQ.



Code: 218
Supported n. of lamps: 12
Power supply
13X2W/110÷240V - Iout 500mA (7X2W@110V)
IP67 CLASS II SELV.