

# 105171143

Product Sheet

# ares

THE OUTDOOR BY FLOS

ARES s.r.l - Socio Unico

v.le dell'Artigianato n.24 - 20881 Bernareggio - MB (Italy)


www.aresill.net - flos.outdoor@flos.com

## Martina Aqua

Adjustable spotlight. Configuration: AISI 316L stainless steel structure and adjustable bracket. Glass diffuser: transparent or sandblasted with silkscreen border, fixed through a robotic gluing system. Protection rating: IP68 (1000mm). In compliance with EN60598-1 standards. Class of insulation: III. Installation: the luminaire is equipped with 5000mm cable. Martina Aqua 24V and Maxi Martina Aqua 24V are equipped with a dc/dc highly efficient resin-coated converter that removes electromagnetic interference and protects against polarity reversal and sudden voltage peak. Parallel wiring required. Mini Martina Aqua, Martina Aqua RGB and Maxi Martina Aqua RGB requires connection in series. SELV equivalent remote power supply required. We recommend the use of a connection system with a protection degree greater than or equal to the protection degree of the luminaire.

IP68 (1MT) 

### Available Colors for this Version



MiniMartina Aqua Power LED / Inox 316L  
Underwater - Transparent Glass -  
Adjustable - Medium Beam 30°

### Warnings

#### Underwater



Pre-wired with approx  
5000mm of cable.




Remote electronic power  
supply



Protection against impact.  
IK 05 - 0,70 joule MiniMartina  
316L  
IK 07 - 2,00 joule Martina  
316L/MaxiMartina 316L

### Light Flux, Placement



### Product Code Details

# 105171143

Light Source



NATURAL WHITE 4000K POWER LED 1,1W/350mA

Total power 1,1W

LED lm 130 ÷ OUTPUT lm 110

CRI>80

Remote electronic power supply to be ordered

Dimmable on request, acc.: 184



## Accessories

---



Code: 136  
Ground spike  
H 200 mm



Code: 184  
Supported n. of lamps: 16  
Power supply  
16X1W/110÷240V - Iout 350mA (12X1W@110V)  
IP67 CLASS II SELV.



Code: 106  
Supported n. of lamps: 6  
Power supply dual function  
Vout 24Vdc: 8W/100÷240V  
Iout 350mA: 6X1W/100÷240V - IP65 CLASS II  
SELV EQ.