

# 105172144

Product Sheet

## ares

THE OUTDOOR BY FLOS

ARES s.r.l - Socio Unico


v.le dell'Artigianato n.24 - 20881 Bernareggio - MB (Italy)

www.aresill.net - flos.outdoor@flos.com

## Martina Aqua


Adjustable spotlight. Configuration: AISI 316L stainless steel structure and adjustable bracket. Glass diffuser: transparent or sandblasted with silkscreen border, fixed through a robotic gluing system. Protection rating: IP68 (1000mm). In compliance with EN60598-1 standards. Class of insulation: III. Installation: the luminaire is equipped with 5000mm cable. Martina Aqua 24V and Maxi Martina Aqua 24V are equipped with a dc/dc highly efficient resin-coated converter that removes electromagnetic interference and protects against polarity reversal and sudden voltage peak. Parallel wiring required. Mini Martina Aqua, Martina Aqua RGB and Maxi Martina Aqua RGB requires connection in series. SELV equivalent remote power supply required. We recommend the use of a connection system with a protection degree greater than or equal to the protection degree of the luminaire.

Martina Aqua Power LED / Inox 316L  
Underwater - Transparent Glass -  
Adjustable - Wide Beam 50°



IP68 (1MT)    

Available Colors for this Version



Warnings

Underwater



Pre-wired with approx 5000mm of cable.



Remote electronic power supply



Protection against impact.  
IK 05 - 0,70 joule MiniMartina 316L  
IK 07 - 2,00 joule Martina 316L/MaxiMartina 316L

Light Flux, Placement



Product Code Details

# 105172144

Light Source



NATURAL WHITE 4000K POWER LEDs 3,3W/24Vdc

Total power 4,5W

LED lm 342 ÷ OUTPUT lm 243

CRI>80

Remote electronic power supply to be ordered



## Accessories



Code: 136  
Ground spike  
H 200 mm



Code: 215  
3/4 way terminal block 3 poles IP68  
(Ø 5,5÷12 mm cable)



Code: 236  
2 way terminal block 3 poles IP68  
(Ø 5,5÷12 mm cable)



Code: 106  
Supported n. of lamps: 1  
Power supply dual function  
Vout 24Vdc: 8W/100÷240V  
Iout 350mA: 6X1W/100÷240V - IP65 CLASS II  
SELV EQ.



Code: 175  
Supported n. of lamps: 2  
Power supply  
10W/110÷240V - 24Vdc  
IP67 CLASS II SELV.



Code: 147  
Supported n. of lamps: 3  
Power supply  
20W/220÷240V - 24Vdc  
IP67 CLASS II SELV.



Code: 155  
Supported n. of lamps: 7  
Power supply  
50W/120÷240V - 24Vdc  
IP67 CLASS II SELV.



Code: 110  
Supported n. of lamps: 14  
Power supply  
70W/220÷240V - 24Vdc  
IP67 CLASS II SELV EQ.