
**Product Sheet** 

# Midna

Luminaire for installation on wall - surface mounted. Configuration: polycarbonate structure and die-cast aluminium cover and base, EN AB-47100 alloy (low copper content) Double layer coating for high resistance to corrosion: the aluminium components are painted with a double coat using powders that are compliant with QUALICOAT standards: a first layer of epoxy powder (with excellent chemical and mechanical resistance) and a second finishing layer of polyester powder (resistant to UV rays and atmospheric agents). The entire painting process of the aluminium fitting starts from components that have been sandblasted in advance to make the surface more porous and increase the adherence of the paint. Ares effects alkaline and acid washing to clean the surfaces completely, then tines with demineralised water to remove any residue particles, subsequently a chemical conversion treatment is done to protect against rusting. Protection rating: IP65 In compliance with EN 60598-1 standards Class of insulation: I Installation: wiring through two cable holders (8mm-dd>13mm cables). Outdoor use requires suitable flexible cables assuring the watertightness of the cable holder.

### Midna / Unidirectional





### **Product Code Details**



Light Source



TC-DEL 18W G24q-2 Electronic ballast






ARES s.r.l - Socio Unico v.le dell'Artigianato n.24 - 20881 Bernareggio - MB (Italy) www.aresill.net - flos.outdoor@flos.com

# IP65 𝖳 ⊕ €€

### Available Colors for this Version



### Warnings





Wall fitting

Protection against impact. IK 09 - 10,00 joule

### Light Flux, Placement



#### The fitting is equipped with 2 cable input.

This product has no accessories