

529005

Product Sheet

ares


THE OUTDOOR BY FLOS

ARES s.r.l - Socio Unico
v.le dell'Artigianato n.24 - 20881 Bernareggio - MB (Italy)
www.aresill.net - flos.outdoor@flos.com

Midna

Luminaire for installation on wall - surface mounted. Configuration: polycarbonate structure and die-cast aluminium cover and base, EN AB-47100 alloy (low copper content) Double layer coating for high resistance to corrosion: the aluminium components are painted with a double coat using powders that are compliant with QUALICOAT standards: a first layer of epoxy powder (with excellent chemical and mechanical resistance) and a second finishing layer of polyester powder (resistant to UV rays and atmospheric agents). The entire painting process of the aluminium fitting starts from components that have been sandblasted in advance to make the surface more porous and increase the adherence of the paint. Ares effects alkaline and acid washing to clean the surfaces completely, then rinses with demineralised water to remove any residue particles, subsequently a chemical conversion treatment is done to protect against rusting. Protection rating: IP65 In compliance with EN 60598-1 standards Class of insulation: I Installation: wiring through two cable holders (8mm- \varnothing <13mm cables). Outdoor use requires suitable flexible cables assuring the watertightness of the cable holder.

Midna / Bidirectional



Product Code Details

529005

Light Source



TC-DEL 18W G24q-2
Electronic ballast



IP65   

Available Colors for this Version



Warnings

Wall



Wall fitting



The fitting is equipped with 2 cable input.



Protection against impact.
IK 09 - 10,00 joule

Light Flux, Placement



Accessories

This product has no accessories