

# 525133

Product Sheet


**ares**  
THE OUTDOOR BY FLOS

ARES s.r.l - Socio Unico  
v.le dell'Artigianato n.24 - 20881 Bernareggio - MB (Italy)  
www.aresill.net - flos.outdoor@flos.com

## Perseo 30

Adjustable projector for installation on wall or on pole. Configuration: die-cast aluminium structure. EN AB-47100 alloy (low copper content). Glass diffuser: extra-clear, fixed to the frame through a robotic gluing system. Graduated stainless steel fixing plate for a precise adjustment. Double layer coating for high resistance to corrosion: the aluminium components are painted with a double coat using powders which are compliant with QUALICOAT standards: a first layer of epoxy powder (with excellent chemical and mechanical resistance) and a second finishing layer of polyester powder (resistant to UV rays and atmospheric agents). The entire painting process of the aluminium fitting starts from components which have been sand-blasted in advance to make the surface more porous and increase the adherence of the paint. Ares effects alkaline and acid washing to clean the surfaces completely, then rinses with demineralised water to remove any residue particles, subsequently a chemical conversion treatment is done to protect against rusting. Protection rating: IP65. In compliance with EN60598-1 standards. Class of insulation: I. Installation: wiring through an M20x1.5 metal cable gland (7mm- $\varnothing$ <13mm cables). Outdoor use requires suitable flexible cables assuring the watertightness of the cable gland.

### Perseo30 Power LED / Adjustable - Narrow beam 10°



### Product Code Details

## 525133

Light Source



WARM WHITE 3000K POWER LEDs 48W/220÷240V  
Total power 53W  
LED lm 4173 ÷ OUTPUT lm 3832  
CRI>80  
Integral electronic power supply



IP65

### Available Colors for this Version



### Warnings

#### Projector



Floor installation



The fitting is equipped with 1 cable input



Wall fitting



Protection against impact. IK 07 - 02,00 joule

#### Pole Top



Installation on pole



Protection against impact. IK 07 - 02,00 joule



The fitting is equipped with 1 cable input

### Light Flux, Placement



# Accessories



Code: 78  
Single bracket 180 mm  
for pole Ø 102 mm (codes: 4140, 4145, 4150, 4155)



Code: 90  
Double bracket 180 mm  
Proper to pole ø 102 mm, code: 4140, 4145, 4150, 4155



Code: 79  
Single bracket 500 mm  
for pole Ø 102 mm (codes: 4140, 4145, 4150, 4155)



Code: 89  
Double bracket 500 mm  
Proper to pole ø 102 mm, code: 4140, 4145, 4150, 4155



Code: 93  
Single bracket 180 mm  
for pole Ø 60 mm (codes: 1005, 1009, 1105, 1109)



Code: 95  
Double bracket 180 mm  
Proper to pole ø 60 mm, code: 1005, 1009, 1105, 1109



Code: 94  
Single bracket 500 mm  
for pole Ø 60 mm (codes: 1005, 1009, 1105, 1109)



Code: 96  
Double bracket 500 mm  
Proper to pole ø 60 mm, code: 1005, 1009, 1105, 1109



Code: 112  
Single bracket 180 mm  
for pole Ø 76 mm (codes: 248, 249, 250, 251)



Code: 114  
Double bracket 180 mm  
for pole Ø 76 mm



Code: 113  
Single bracket 500 mm  
for pole Ø 76 mm (codes: 248, 249, 250, 251)



Code: 115  
Double bracket 500 mm  
for pole Ø 76 mm



Code: 116  
Base plate and pole fixing bolts  
230 x 230 x H 200 mm




Code: 167  
Wall Washer Visor




Code: 168  
Anti Vandal Louvre




Code: 181  
Wall bracket  
1000 mm




Code: 248  
Pole with Base and Access Door  
With Terminal Block 4x1,5-16mmq  
ø76 mm  
H 3500 mm  
.6 grey  
.3 anthracite



Code: 249  
Pole with Base and Access Door  
With Terminal Block 4x1,5-16mmq  
ø76 mm  
H 4500 mm  
.6 grey  
.3 anthracite



Code: 250  
In-Ground Pole (+500 mm Root)  
With Access Door With Terminal Block 4x1,5-16mmq  
ø76 mm  
H 3500 mm (+500 mm)  
.6 grey  
.3 anthracite




Code: 251  
In-Ground Pole (+500 mm Root)  
With Access Door With Terminal Block 4x1,5-16mmq  
ø76 mm  
H 4500 mm (+500 mm)  
.6 grey  
.3 anthracite




Code: 4140  
 Pole with Base and Access Door  
 With Terminal Block 4x1,5-16mmq  
 ø102mm  
 H 4000mm  
 .6 grey  
 .3 anthracite




Code: 4150  
 Pole with Base and Access Door  
 With Terminal Block 4x1,5-16mmq  
 ø102mm  
 H 5000mm  
 .6 grey  
 .3 anthracite



Code: 4145  
 In-Ground Pole (+500 mm Root)  
 With Access Door With Terminal Block 4x1,5-  
 16mmq  
 ø102mm  
 H 4000mm (+500 mm)  
 .6 grey  
 .3 anthracite



Code: 4155  
 In-Ground Pole (+500 mm Root)  
 With Access Door With Terminal Block 4x1,5-  
 16mmq  
 ø102mm  
 H 5000mm (+500 mm)  
 .6 grey  
 .3 anthracite



Code: 237  
 SPD: (Surge Protection Device) 275Vac  
 Maximum discharge current 10KA (8/20µs)  
 Maximum operating current 5A  
 Suitable for series connection - IP66