

525003

Product Sheet

ares

THE OUTDOOR BY FLOS

ARES s.r.l - Socio Unico
v.le dell'Artigianato n.24 - 20881 Bernareggio - MB (Italy)
www.aresill.net - flos.outdoor@flos.com

Perseo 4


Adjustable projector for installation on wall, on pole/bracket or on floor. Configuration: die-cast aluminium structure, EN AB-47100 alloy (low copper content). Glass diffuser: extra-clear or sandblasted. Double layer coating for high resistance to corrosion: the aluminium components are painted with a double coat using powders which are compliant with QUALICOAT standards: a first layer of epoxy powder (with excellent chemical and mechanical resistance) and a second finishing layer of polyester powder (resistant to UV rays and atmospheric agents). The entire painting process of the aluminium fitting starts from components which have been sand-blasted in advance to make the surface more porous and increase the adherence of the paint. Ares effects alkaline and acid washing to clean the surfaces completely, then rinses with demineralised water to remove any residue particles, subsequently a chemical conversion treatment is done to protect against rusting. Protection rating: IP65. In compliance with EN60598-1 standards. Class of insulation: II. Installation: the luminaire is equipped with 700mm cable for an easy-to-make connection. The bracket/pole is supplied with a 2-way terminal block for 3-conductor cables - IP68. We recommend the use of a connection system with a protection degree greater than or equal to the protection degree of the luminaire.

IP65  

Available Colors for this Version



Perseo4 Mid-Power LED / Adjustable - Sandblasted Glass



Product Code Details

525003

Light Source



WARM WHITE 3000K MID-POWER LEDs 6,6W/100÷240V
Total power 9W
LED lm 899 ÷ OUTPUT lm 468
CRI>80
Integral electronic power supply



Warnings

Projector



Floor installation



Pre-wired with approx 700mm of cable.



Wall fitting



Protection against impact. IK 05 - 0,70 joule

Pole Top



Installation on pole



Protection against impact. IK 05 - 0,70 joule



Pre-wired with approx 700mm of cable.

Light Flux, Placement



Accessories



Code: 136
Ground spike
H 200 mm



Code: 157
Wall bracket
300 mm



Code: 158
Wall bracket
600 mm



Code: 237
SPD: (Surge Protection Device) 275Vac
Maximum discharge current 10KA (8/20 μ s)
Maximum operating current 5A
Suitable for series connection - IP66