

525032

Product Sheet

ares

THE OUTDOOR BY FLOS

ARES s.r.l - Socio Unico


v.le dell'Artigianato n.24 - 20881 Bernareggio - MB (Italy)

www.aresill.net - flos.outdoor@flos.com

Perseo 9

Adjustable projector for installation on wall, on pole/ bracket or on floor. Configuration: die-cast aluminium structure, EN AB-47100 alloy (low copper content). Glass diffuser: extra-clear or sandblasted, fixed to the aluminium frame through a robotic gluing system. Double layer coating for high resistance to corrosion: the aluminium components are painted with a double coat using powders which are compliant with QUALICOAT standards: a first layer of epoxy powder (with excellent chemical and mechanical resistance) and a second finishing layer of polyester powder (resistant to UV rays and atmospheric agents). The entire painting process of the aluminium fitting starts from components which have been sand-blasted in advance to make the surface more porous and increase the adherence of the paint. Ares effects alkaline and acid washing to clean the surfaces completely, then rinses with demineralised water to remove any residue particles, subsequently a chemical conversion treatment is done to protect against rusting. Protection rating: IP65. In compliance with EN60598-1 standards. Class of insulation: I. Installation: the luminaire is equipped with 2000mm cable for an easy-to-make connection. The bracket/pole is supplied with a 2-way terminal block for 3-conductor cables - IP68. We recommend the use of a connection system with a protection degree greater than or equal to the protection degree of the luminaire.

Perseo9 Mid-Power LED / Adjustable - Sandblasted Glass



Product Code Details

525032

Light Source



NATURAL WHITE 4000K MID-POWER LEDs 8,8W/220÷240V

Total power 11W

LED lm 1258 ÷ OUTPUT lm 655

CRI>80

Integral electronic power supply



IP65  

Available Colors for this Version



Warnings

Projector



Floor installation



Pre-wired with approx 200mm of cable



Wall fitting



Protection against impact. IK 06 - 1,00 joule

Pole Top



Installation on pole



Protection against impact. IK 06 - 1,00 joule



Pre-wired with approx 200mm of cable

Light Flux, Placement



Accessories



Code: 136
Ground spike
H 200 mm



Code: 161
Wall bracket
300 mm



Code: 162
Wall bracket
600 mm




Code: 177
ø48 - Poles with Base
H 500 mm
Combinable with Base plate and fixing bolts,
code 182



Code: 178
ø48 - Poles with Base
H 800 mm
Combinable with Base plate and fixing bolts,
code 182



Code: 182
Base plate and fixing bolts
Ø 110 x H 160 mm



Code: 237
SPD: (Surge Protection Device) 275Vac
Maximum discharge current 10KA (8/20µs)
Maximum operating current 5A
Suitable for series connection - IP66