936784

Product Sheet




ARES s.r.I - Socio Unico v.le dell'Artigianato n.24 - 20881 Bernareggio - MB (Italy) www.aresill.net - flos.outdoor@flos.com

Mini Silvia Post


Outdoor luminaire for installation on floor. Configuration: die-cast aluminium structure EN AB-47100 alloy (low copper content), extruded aluminium pole, borosilicate transparent or sandblasted glass, moulded silicone gaskets. Double layer coating for high resistance to corrosion: The aluminium components are painted with a double coat using powders which are complaint with QUALICOAT standards: a first layer of epoxy powder (with excellent chemical and mechanical resistance) and a second finishing layer of polyester powder (resistant to UV rays and atmospheric agents). The entire painting process of the aluminium fitting starts from components which have been sand-blasted in advance to make the surface more porous and increase the adherence of the paint. Ares effects alkaline and acid washing to clean the surfaces completely, then rinses with demineralised water to remove any residue particles, subsequently a chemical conversion treatment is done to protect against rusting. Protection Rating: IP65. In compliance with EN 60598-1 standards. Class of insulation: I. Installation: the luminaire is supplied with a piece of cable and an IP68 connector (for cables 5acceptage and a IP68 connector (for cables 5acceptage action-rung acceptage and a IP68 connector (for cables 5acceptage acceptage ac

MiniSilvia on post / H. 550 mm - Transparent Glass - 360° Emission



IP65 ♥ ⊕ C€

Available Colors for this Version



Warnings

Bollard



Bollard light



The fitting is equipped with 1 cable input

Protection against impact. IK 07 - 02,00 joule

Light Flux, Placement





Product Code Details

936784

Light Source



HIT-TC-CE 35W G8,5 Electronic ballast





Code: 21 Base plate and pole fixing bolts 174 x H 200 mm