# 850121

Product Sheet

Silvia

Outdoor luminaire for installation on wall, ceiling and floor. Configuration: die-cast aluminium structure EN AB-47100 alloy (low copper content), borosilicate transparent or sandblasted glass, moulded silicone gaskets. Double layer coating for high resistance to corrosion: The aluminium components are painted with a double coat using powders which are complaint with QUALICOAT standards: a first layer of epoxy powder (with excellent chemical and mechanical resistance) and a second finishing layer of polyester powder (resistant to UV rays and atmospheric agents).The entire painting process of the aluminium fitting starts from components which have been sand-blasted in advance to make the surface more porous and increase the adherence of the paint. Ares effects alkaline and acid washing to clean the surfaces completely, then rinses with demineralised water to remove any residue particles, subsequently a chemical conversion treatment is done to protect against rusting. Protection Rating: IP65. In compliance with EN 60598-1 standards. Class of insulation: I. Installation: wiring through M20x1,5 cable gland (6<ø<12mm cables) placed under the head of the luminaire. Outdoor use requires suitable flexible cables assuring the watertightness of the cable gland.

IP65   CE

Available Colors for this Version

1. white	6. grey
3. anthracite	4. black
18. deep brown	

Silvia / Sandblasted Glass - 120° Emission

Ø180 / 245 / 54

Product Code Details

850121

Light Source

QT 32 100W E27

D

Warnings

Bollard

Bollard light	Ceiling fitting
The fitting is equipped with 1 cable input	Protection against impact. IK 07 - 02,00 joule

Ceiling

Ceiling fitting	The fitting is equipped with 1 cable input
Protection against impact. IK 07 - 02,00 joule	

Wall

Wall fitting	Ceiling fitting
The fitting is equipped with 1 cable input	Protection against impact. IK 07 - 02,00 joule

Light Flux, Placement

Accessories

This product has no accessories