

**Product Sheet** 




ARES s.r.I - Socio Unico v.le dell'Artigianato n.24 - 20881 Bernareggio - MB (Italy) www.aresill.net - flos.outdoor@flos.com

## Silvia

Outdoor luminaire for installation on wall, ceiling and floor. Configuration: die-cast aluminium structure EN AB-47100 alloy (low copper content), borosilicate transparent or sandblasted glass, moulded silicone gaskets. Double layer coating for high resistance to corrosion: The aluminium components are painted with a double coat using powders which are complaint with QUALICOAT standards: a first layer of epoxy powder (with excellent chemical and mechanical resistance) and a second finishing layer of polyester powder (resistant to UV rays and atmospheric agents). The entire painting process of the aluminium fitting starts from components which have been sand-blasted in advance to make the surface more porous and increase the adherence of the paint. Ares effects alkaline and acid washing to clean the surfaces completely, then rinses with demineralised water to remove any residue particles, subsequently a chemical conversion treatment is done to protect against rusting. Protection Rating: IP65. In compliance with EN 60598-1 standards. Class of insulation: I. Installation: wiring through M20x1,5 cable gland (6-a-12mm cables) placed under the head of the luminaire. Outdoor use requires suitable flexible cables assuring the watertightness of the cable gland.

### Silvia / Sandblasted Glass - 360° Emission





#### **Product Code Details**

# 859800

Light Source




TC-TEL 26W GX24q-3 Electronic ballast



# IP65 ♥ ⊕ C€

### Available Colors for this Version



#### Warnings

#### **Bollard**



Bollard light



Ceiling fitting



The fitting is equipped with 1 cable input



Protection against impact. IK 07 - 02,00 joule

#### Ceiling



Ceiling fitting



The fitting is equipped with 1 cable input



Protection against impact. IK 07 - 02,00 joule

#### Nall



Wall fitting



Ceiling fitting



The fitting is equipped with 1 cable input



Protection against impact. IK 07 - 02,00 joule

### Light Flux, Placement









This product has no accessories