

859821

Product Sheet

ares
THE OUTDOOR BY FLOS

ARES s.r.l - Socio Unico
v.le dell'Artigianato n.24 - 20881 Bernareggio - MB (Italy)
www.aresill.net - flos.outdoor@flos.com

Silvia


Outdoor luminaire for installation on wall, ceiling and floor. Configuration: die-cast aluminium structure EN AB-47100 alloy (low copper content), borosilicate transparent or sandblasted glass, moulded silicone gaskets. Double layer coating for high resistance to corrosion: The aluminium components are painted with a double coat using powders which are compliant with QUALICOAT standards: a first layer of epoxy powder (with excellent chemical and mechanical resistance) and a second finishing layer of polyester powder (resistant to UV rays and atmospheric agents). The entire painting process of the aluminium fitting starts from components which have been sand-blasted in advance to make the surface more porous and increase the adherence of the paint. Ares effects alkaline and acid washing to clean the surfaces completely, then rinses with demineralised water to remove any residue particles, subsequently a chemical conversion treatment is done to protect against rusting. Protection Rating: IP65. In compliance with EN 60598-1 standards. Class of insulation: I. Installation: wiring through M20x1,5 cable gland (6<ø<12mm cables) placed under the head of the luminaire. Outdoor use requires suitable flexible cables assuring the watertightness of the cable gland.

IP65   CE

Available Colors for this Version



Silvia / Sandblasted Glass - 120° Emission



Product Code Details

859821

Light Source



TC-TEL 26W GX24q-3
Electronic ballast



Warnings

Bollard



Bollard light



The fitting is equipped with 1 cable input



Ceiling fitting



Protection against impact.
IK 07 - 02,00 joule

Ceiling



Ceiling fitting



Protection against impact.
IK 07 - 02,00 joule



The fitting is equipped with 1 cable input

Wall



Wall fitting



The fitting is equipped with 1 cable input



Ceiling fitting



Protection against impact.
IK 07 - 02,00 joule

Light Flux, Placement



Accessories

This product has no accessories