

541008

Product Sheet

ares

THE OUTDOOR BY FLOS

ARES s.r.l - Socio Unico


v.le dell'Artigianato n.24 - 20881 Bernareggio - MB (Italy)

www.aresill.net - flos.outdoor@flos.com

Spock

Adjustable projector for installation on ceiling, wall or floor. Configuration: die-cast aluminium structure, EN AB-47100 alloy (low copper content) and AISI 316L stainless steel fixing bracket. Glass diffuser: extra clear with silkscreen border, fixed through a robotic gluing system. The luminaire has three connected parts: wiring unit (silicone gasket), heat sink and emitting unit (silicone glue). A graduated fixing plate allows a precise adjustment of the emitting unit. Double layer coating for high resistance to corrosion: the aluminium components are painted with a double coat using powders which are compliant with QUALICOAT standards: a first layer of epoxy powder (with excellent chemical and mechanical resistance) and a second finishing layer of polyester powder (resistant to UV rays and atmospheric agents). The entire painting process of the aluminium fitting starts from components which have been sand-blasted in advance to make the surface more porous and increase the adherence of the paint. Ares effects alkaline and acid washing to clean the surfaces completely, then rinses with demineralised water to remove any residue particles, subsequently a chemical conversion treatment is done to protect against rusting. Protection rating: IP66. In compliance with EN60598-1 standards. Class of insulation: I. Installation: the luminaire is equipped with 1000mm of cable for an easy-to-make connection. We recommend the use of a connection system with a protection degree greater than or equal to the protection degree of the luminaire.

Spock95 CoB LED - Adjustable - Medium Beam 20°



IP66   

Available Colors for this Version



Warnings

Projector



Floor installation

Ceiling fitting

Protection against impact.
IK 07 - 02,00 joule



Wall fitting

Pre-wired with approx
1000mm of cable.

Light Flux, Placement



Product Code Details

541008

Light Source



WARM WHITE 3000K CoB LED 24W/220÷240V

Total power 29W

LED lm 3249 ÷ OUTPUT lm 2302

CRI >80

Integral electronic power supply




Accessories



Code: 206
Visor
Ø 95 mm



Code: 209
Flood diffuser
Ø 95 mm



Code: 212
Anti-glare louvre
Ø 95 mm



Code: 203
Kit of 2 ground spikes
H 220 mm



Code: 215
3/4 way terminal block 3 poles IP68
(Ø 5,5÷12 mm cable)



Code: 236
2 way terminal block 3 poles IP68
(Ø 5,5÷12 mm cable)



Code: 237
SPD: (Surge Protection Device) 275Vac
Maximum discharge current 10KA (8/20µs)
Maximum operating current 5A
Suitable for series connection - IP66