

10017712

Product Sheet


ares
THE OUTDOOR BY FLOS

ARES s.r.l - Socio Unico
v.le dell'Artigianato n.24 - 20881 Bernareggio - MB (Italy)
www.aresill.net - flos.outdoor@flos.com

Tapioca

Square or round luminaire - for installation in wall, ceiling or ground - recessed.
Configuration: die-cast aluminium structure, EN AB-47100 alloy (low copper content).
Anodized aluminium frame - only round. Glass diffuser: transparent or sandblasted, fixed to the aluminium body through a robotic gluing system. Double layer coating for high resistance to corrosion: the aluminium components are painted with a double coat using powders which are compliant with QUALICOAT standards: a first layer of epoxy powder (with excellent chemical and mechanical resistance) and a second finishing layer of polyester powder (resistant to UV rays and atmospheric agents). The entire painting process of the aluminium fitting starts from components which have been sandblasted in advance to make the surface more porous and increase the adherence of the paint. Ares effects alkaline and acid washing to clean the surfaces completely, then rinses with demineralised water to remove any residue particles, subsequently a chemical conversion treatment is done to protect against rusting. Protection rating: IP67 In compliance with EN 60598-1 standards Class of insulation: III Installation: the luminaire is equipped with a piece of cable for an easy-to-make connection and an H2O STOP device. Tapioca 24V is equipped with a dc/dc highly efficient resin-coated converter that removes electromagnetic interference and allows parallel wiring. The luminaire is protected against polarity reversal and sudden voltage peak. Installation requires a dedicated box to be ordered separately. It is important to provide a >200mm gravel layer or a drain system (for concrete surface) to ensure good drainage and to avoid water stagnation. We recommend the use of a connection system with a protection degree greater than or equal to the protection degree of the luminaire

Tapioca Power LED / Ø 40mm - Transparent Glass - Narrow Beam 10°



Product Code Details

10017712

Light Source



NATURAL WHITE 4000K POWER LED 1,6W/12÷24Vdc

Total power 2,3W

LED lm 195 ÷ OUTPUT lm 138

CRI >80

Remote electronic power supply to be ordered



IP67

Warnings

Ground Recessed



Recessed ground fitting



Do not install in hollow areas



Installation requires a 20 cm water drainage layer (gravel)



Protection against water ingress from the cable. (not for RGB versions)



Static load: 500Kg walk over (version without frame)
Static load: 2000Kg walk over (version with frame)



Protection against impact. IK 08 - 5,00 joule
IK 06 - 1,00 joule* (only version Ø 55 mm)



Pre-wired with approx 200mm of cable



Remote device required



Glass surface temperature

Wall Recessed



Protection against water ingress from the cable. (not for RGB versions)



Protection against impact. IK 08 - 5,00 joule
IK 06 - 1,00 joule* (only version Ø 55 mm)



Recessed wall fitting



Pre-wired with approx 200mm of cable



Remote device required

Ceiling Recessed



Protection against water ingress from the cable. (not for RGB versions)



Protection against impact. IK 08 - 5,00 joule
IK 06 - 1,00 joule* (only version Ø 55 mm)



Installation in concrete ceiling: box for installation required.



Pre-wired with approx 200mm of cable



Remote device required

Light Flux, Placement



Accessories



Code: 98
Box for installation
Ø 75 H 90 mm



Code: 150
Supported n. of lamps: 1
Power supply dual function
Vout 24Vdc: 8W/100÷240V
Iout 350mA: 6X1W/100÷240V
IP20 CLASS II SELV EQ.



Code: 106
Supported n. of lamps: 1
Power supply dual function
Vout 24Vdc: 8W/100÷240V
Iout 350mA: 6X1W/100÷240V - IP65 CLASS II SELV EQ.



Code: 87
Supported n. of lamps: 4
Power supply
10W/110÷240V - 24Vdc
IP20 CLASS II SELV.



Code: 175
Supported n. of lamps: 4
Power supply
10W/110÷240V - 24Vdc
IP67 CLASS II SELV.



Code: 147
Supported n. of lamps: 5
Power supply
20W/220÷240V - 24Vdc
IP67 CLASS II SELV.



Code: 155
Supported n. of lamps: 14
Power supply
50W/120÷240V - 24Vdc
IP67 CLASS II SELV.



Code: 110
Supported n. of lamps: 29
Power supply
70W/220÷240V - 24Vdc
IP67 CLASS II SELV EQ.