57303

Product Sheet

Tau

Light for installation on wall or ceiling - surface mounted. Configuration: polycarbonate tube, opal or transparent, with anti-UV filter. Polycarbonate fixing brackets and anodized aluminium closing caps. Protection Rating: IP65 In compliance with EN 60588-1 standards Class of insulation: III Installation: the luminaire is supplied with a screw connector and requires the use of a feeding cable (direct to power supply or for end-to-end connection) to be ordered separately. Parallel wiring required. Maximum end-to-end sequence: 5000mm.


Tau Low Power LED / L. 554 - Opal Diffuser



IP65 ♥ � €

Warnings





Remote device required

Ceiling fitting



feeding cable (acc. code 172, 173 or 174)

Wall fitting

Protection against impact. IK 06 - 1,00 joule

Installation requires a

Light Flux, Placement



Product Code Details



Light Source



WARM WHITE 3000K LOW POWER LEDs 5W/24Vdc Total power 5W LED Im 420 ÷ OUTPUT Im 196 CRI>80 Remote electronic power supply to be ordered Dimmable on request, acc.: 144,176





ARES s.r.l - Socio Unico v.le dell'Artigianato n.24 - 20881 Bernareggio - MB (Italy) www.aresill.net - flos.outdoor@flos.com

Accessories



Code: 172 Supply cable L. 2000 mm Single connector



Code: 174 Supply cable L. 200 mm Double connector

Supported n. of lamps: 1

Supported n. of lamps: 2

Power supply 10W/110÷240V - 24Vdc

IP67 CLASS II SELV.

Power supply dual function Vout 24Vdc: 8W/100÷240V

lout 350mA: 6X1W/100÷240V - IP65 CLASS II

Code: 106

SELV EQ.

Code: 175



Code: 173 Supply cable L. 80 mm Double connector



Code: 150 Supported n. of lamps: 1 Power supply dual function Vout 24Vdc: 8W/100÷240V Iout 350mA: 6X1W/100÷240V IP20 CLASS II SELV EQ.



Code: 87 Supported n. of lamps: 2 Power supply 10W/110÷240V - 24Vdc IP20 CLASS II SELV.



Code: 144 Supported n. of lamps: 3 Power supply 17W/110+240V - 24Vdc (15W@110V) IP20 CLASS II SELV.



Code: 176 Supported n. of lamps: 3 Power supply 17W/110+240V - 24Vdc (15W@110V) IP67 CLASS II SELV.



Code: 155 Supported n. of lamps: 10 Power supply 50W/120÷240V - 24Vdc IP67 CLASS II SELV.



Code: 156 Supported n. of lamps: 18 Power supply 100W /120÷240V - 24Vdc IP67 CLASS II SELV.



Code: 147 Supported n. of lamps: 4 Power supply 20W/220÷240V - 24Vdc IP67 CLASS II SELV.



Code: 110 Supported n. of lamps: 14 Power supply 70W/220÷240V - 24Vdc IP67 CLASS II SELV EQ.