

523042

Product Sheet

ares



THE OUTDOOR BY FLOS

ARES s.r.l - Socio Unico
v.le dell'Artigianato n.24 - 20881 Bernareggio - MB (Italy)
www.aresill.net - flos.outdoor@flos.com

Tau

Light for installation on wall or ceiling - surface mounted. Configuration: polycarbonate tube, opal or transparent, with anti-UV filter. Polycarbonate fixing brackets and anodized aluminium closing caps. Protection Rating: IP65 In compliance with EN 60598-1 standards Class of insulation: III Installation: the luminaire is supplied with a screw connector and requires the use of a feeding cable (direct to power supply or for end-to-end connection) to be ordered separately. Parallel wiring required. Maximum end-to-end sequence: 5000mm.

Tau Low Power LED / L. 1054 - Transparent Diffuser



IP65   

Warnings

Wall/Ceiling



Ceiling fitting



Wall fitting



Protection against water ingress from the cable



Remote device required



Installation requires a feeding cable (acc. code 172, 173 or 174)



Protection against impact. IK 06 - 1,00 joule

Light Flux, Placement



Product Code Details

523042

Light Source



NATURAL WHITE 4000K LOW POWER LEDs 10W/24Vdc

Total power 10W

LED lm 840 ÷ OUTPUT lm 768

CRI>80

Remote electronic power supply to be ordered

Dimmable on request, acc.: 144,176



Accessories



Code: 172
Supply cable L. 2000 mm
Single connector



Code: 173
Supply cable L. 80 mm
Double connector



Code: 174
Supply cable L. 200 mm
Double connector



Code: 144
Supported n. of lamps: 1
Power supply
17W/110÷240V - 24Vdc
(15W@110V) IP20 CLASS II SELV.



Code: 176
Supported n. of lamps: 1
Power supply
17W/110÷240V - 24Vdc
(15W@110V) IP67 CLASS II SELV.



Code: 147
Supported n. of lamps: 2
Power supply
20W/220÷240V - 24Vdc
IP67 CLASS II SELV.



Code: 155
Supported n. of lamps: 5
Power supply
50W/120÷240V - 24Vdc
IP67 CLASS II SELV.



Code: 110
Supported n. of lamps: 7
Power supply
70W/220÷240V - 24Vdc
IP67 CLASS II SELV EQ.



Code: 156
Supported n. of lamps: 9
Power supply
100W /120÷240V - 24Vdc
IP67 CLASS II SELV.