

# 523043

Product Sheet

# ares

THE OUTDOOR BY FLOS

ARES s.r.l - Socio Unico


v.le dell'Artigianato n.24 - 20881 Bernareggio - MB (Italy)

www.aresill.net - flos.outdoor@flos.com

## Tau

Light for installation on wall or ceiling - surface mounted. Configuration: polycarbonate tube, opal or transparent, with anti-UV filter. Polycarbonate fixing brackets and anodized aluminium closing caps. Protection Rating: IP65 In compliance with EN 60598-1 standards Class of insulation: III Installation: the luminaire is supplied with a screw connector and requires the use of a feeding cable (direct to power supply or for end-to-end connection) to be ordered separately. Parallel wiring required. Maximum end-to-end sequence: 5000mm.

### Tau Low Power LED / L. 1054 - Transparent Diffuser



IP65

### Warnings

#### Wall/Ceiling



Ceiling fitting



Wall fitting



Protection against water ingress from the cable



Installation requires a feeding cable (acc. code 172, 173 or 174)



Remote device required



Protection against impact. IK 06 - 1,00 joule

### Light Flux, Placement



### Product Code Details

# 523043

Light Source



WARM WHITE 3000K LOW POWER LEDs 10W/24Vdc

Total power 10W

LED lm 840 ÷ OUTPUT lm 768

CRI>80

Remote electronic power supply to be ordered

Dimmable on request, acc.: 144,176



## Accessories

---



Code: 172  
Supply cable L. 2000 mm  
Single connector



Code: 173  
Supply cable L. 80 mm  
Double connector



Code: 174  
Supply cable L. 200 mm  
Double connector



Code: 144  
Supported n. of lamps: 1  
Power supply  
17W/110÷240V - 24Vdc  
(15W@110V) IP20 CLASS II SELV.



Code: 176  
Supported n. of lamps: 1  
Power supply  
17W/110÷240V - 24Vdc  
(15W@110V) IP67 CLASS II SELV.



Code: 147  
Supported n. of lamps: 2  
Power supply  
20W/220÷240V - 24Vdc  
IP67 CLASS II SELV.



Code: 155  
Supported n. of lamps: 5  
Power supply  
50W/120÷240V - 24Vdc  
IP67 CLASS II SELV.



Code: 110  
Supported n. of lamps: 7  
Power supply  
70W/220÷240V - 24Vdc  
IP67 CLASS II SELV EQ.



Code: 156  
Supported n. of lamps: 9  
Power supply  
100W /120÷240V - 24Vdc  
IP67 CLASS II SELV.