
っというん

Product Sheet

Tau

Light for installation on wall or ceiling - surface mounted. Configuration: polycarbonate tube, opal or transparent, with anti-UV filter. Polycarbonate fixing brackets and anodized aluminium closing caps. Protection Rating: IP65 In compliance with EN 60588-1 standards Class of insulation: III Installation: the luminaire is supplied with a screw connector and requires the use of a feeding cable (direct to power supply or for end-to-end connection) to be ordered separately. Parallel wiring required. Maximum end-to-end sequence: 5000mm.

Tau Low Power LED / L. 1554 - Transparent Tube




THE OUTDOOR BY FLOS

ARES s.r.l - Socio Unico v.le dell'Artigianato n.24 - 20881 Bernareggio - MB (Italy) www.aresill.net - flos.outdoor@flos.com

IP65 ♥ � €

Warnings





Remote device required

Ceiling fitting



Installation requires a

Wall fitting

feeding cable (acc. code 172, 173 or 174) Protection against impact.



IK 06 - 1,00 joule

Light Flux, Placement



Product Code Details



Light Source



NATURAL WHITE 4000K LOW POWER LEDs 15W/24Vdc Total power 15W LED Im 1260 ÷ OUTPUT Im 1152 CRI>80 Remote electronic power supply to be ordered Dimmable on request, acc.: 144,176



Accessories



Code: 172 Supply cable L. 2000 mm Single connector

Code: 173 Supply cable L. 80 mm Double connector



Code: 174 Supply cable L. 200 mm Double connector

Supported n. of lamps: 1

Code: 176

Power supply 17W/110÷240V - 24Vdc (15W@110V) IP67 CLASS II SELV.



Code: 144 Supported n. of lamps: 1 Power supply 17W/110÷240V - 24Vdc (15W@110V) IP20 CLASS II SELV.



Code: 147 Supported n. of lamps: 1 Power supply 20W/220÷240V - 24Vdc IP67 CLASS II SELV.

Code: 110 Supported n. of lamps: 4 Power supply 70W/220+240V - 24Vdc IP67 CLASS II SELV EQ.

Code: 110



Code: 155 Supported n. of lamps: 3 Power supply 50W/120÷240V - 24Vdc IP67 CLASS II SELV.



Code: 156 Supported n. of lamps: 6 Power supply 100W /120÷240V - 24Vdc IP67 CLASS II SELV.