523073

Product Sheet



THE OUTDOOK BY FLOS

ARES s.r.I - Socio Unico v.le dell'Artigianato n.24 - 20881 Bernareggio - MB (Italy) www.aresill.net - flos.outdoor@flos.com

Tau

Light for installation on wall or ceiling - surface mounted. Configuration: polycarbonate tube, opal or transparent, with anti-UV filter. Polycarbonate fixing brackets and anodized aluminium closing caps. Protection Rating: IP65 In compliance with EN 60598-1 standards Class of insulation: III Installation: the luminaire is supplied with a screw connector and requires the use of a feeding cable (direct to power supply or for end-to-end connection) to be ordered separately. Parallel wiring required. Maximum end-to-end sequence: 5000mm.

Tau Low Power LED / L. 1554 - Opal Diffuser



Product Code Details

523073

Light Source



WARM WHITE 3000K LOW POWER LEDs 15W/24Vdc Total power 15W LED Im 1260 \div OUTPUT Im 589

Remote electronic power supply to be ordered Dimmable on request, acc.: 144,176



IP65 ♥ �(€

Warnings

Wall/Ceiling



Ceiling fitting



Wall fitting



Protection against water ingress from the cable

Remote device required



Installation requires a feeding cable (acc. code 172, 173 or 174)



Protection against impact. IK 06 - 1,00 joule

Light Flux, Placement









Code: 172 Supply cable L. 2000 mm Single connector



Code: 173 Supply cable L. 80 mm Double connector



Code: 174 Supply cable L. 200 mm Double connector



Code: 144 Supported n. of lamps: 1 Power supply 17W/110÷240V - 24Vdc (15W@110V) IP20 CLASS II SELV.



Code: 176 Supported n. of lamps: 1 Power supply 17W/110÷240V - 24Vdc (15W@110V) IP67 CLASS II SELV.



Code: 147 Supported n. of lamps: 1 Power supply 20W/220÷240V - 24Vdc IP67 CLASS II SELV.



Code: 155 Supported n. of lamps: 3 Power supply 50W/120÷240V - 24Vdc IP67 CLASS II SELV.



Code: 110 Supported n. of lamps: 4 Power supply 70W/220÷240V - 24Vdc IP67 CLASS II SELV EQ.



Code: 156 Supported n. of lamps: 6 Power supply 100W /120÷240V - 24Vdc IP67 CLASS II SELV.