10410400

Product Sheet



IP65 ♥ ⊕ C€

7. zinc


ARES s.r.I - Socio Unico v.le dell'Artigianato n.24 - 20881 Bernareggio - MB (Italy) www.aresill.net - flos.outdoor@flos.com

Available Colors for this Version

Viviana

Bollard light. Configuration: hot-dip zinc-coated IPE steel bar (H-frame with base) for high resistance to corrosion. The emission unit, fixed to the upper part of the bar, is composed of a plastic container with zinc-coated cover. Feeding cables are hosted in a hot-dip zinc-coated cover placed on the back side of the bar. Protection Rating: IP65 In compliance with EN 60598-1 standards Class of insulation: I Installation: wiring through two rubber cable glands (8<ø<13mm cables). We recommend installation on a concrete basement or surface, directly with bolts or through the dedicated fixing plate (to be ordered separately).

Viviana Power LED



Bollard

Warnings



Bollard light



The fitting is equipped with 2 cable input.

Protection against impact. IK 10 - 20,00 joule

Light Flux, Placement





Product Code Details

10410400

Light Source



WARM WHITE 3000K POWER LEDs 8W/220÷240V Total power 11W LED Im 900 ÷ OUTPUT Im 241 CRI >80 Integral electronic power supply





Code: 109 Base plated and fixing bolts 200 x 230 x H 210 mm



Code: 237 SPD: (Surge Protection Device) 275Vac Maximum discharge current 10KA (8/20µs) Maximum operating current 5A Suitable for series connection - IP66