

September 2012

Le Perroquet -

Product code:

4834

Technical description:

Adjustable fitting with adapter for track application designed to use low-voltage halogen lamps with flood optic. The projector is made of die-cast aluminium and thermoplastic material. It has an accessory-holding ring able to comprise up to three flat accessories at the same time (e.g. coloured filter, infrared filter and louvre). One more external component can be applied, i.e. an asymmetrical screen, adjustable flaps or an anti-glare screen. All the external accessories can be rotated by 360° with respect to the longitudinal axis of the projector. The device permits a rotation of 360° around the vertical axis, while the inclination can reach 190° with respect to the vertical axis. Aiming is ensured by screw mechanical locks, graduated scales and friction devices. The fitting comes complete with protection glass. The device permits a rotation of 360° around the vertical axis, while the inclination can reach 190° with respect to the vertical axis. Aiming is ensured by screw mechanical locks, graduated scales and friction devices. IP40 for optical assembly.

Installation:

Mains-voltage track installation by an adapter.

Dimension:

D = 156 mm h = 215 mm

Colour:

White (01)|Grey/Black (74)

Weight [Kg]:

2,2

Mounting:

Three circuit track

Wiring:

Electronic transformer and dimmer.

Complies with EN605981 and pertinent regulations

