

Le Perroquet

Design Renzo Piano

iGuzzini

September 2012

Le Perroquet - Projector complete with 150 W HIT control gear

Product code:

4869

Technical description:

Die-cast aluminium and thermoplastic projector with adapter. It can be rotated by 360° with respect to the vertical axis and inclined by 10° upwards and 90° downwards. Mechanical locking devices, graduated scales and adjustable friction devices guarantee the precise positioning of the light beam. The projector is equipped with a mechanical adapter to secure it to the track and a tri-phase adapter for the electrical connection. The luminaire is provided with a set of diaphragms for the emission of circular light beams and can have an optional set of adjustable diaphragms for shaping the light beam itself. All pointing, focusing and routine maintenance operations can be performed without the use of special tools. The luminaire is designed to be used with accessories, such as glass and metal gobos and coloured filters. IP40 for optical assembly.

Installation:

Fitted to an electrified track.

Dimension:

D=170 mm H=350 mm L=483/553 mm

Colour:

White (01)|Grey/Black (74)

Weight [Kg]:

6,8

Mounting:

Three circuit track

Wiring:

Contained inside the luminaire.

Notes:

We recommend the luminaire is installed on suspended tracks with rigid supports.

Complies with EN605981 and pertinent regulations

