

## Mini Reglette

Design iGuzzini

iGuzzini

Last information update: June 2018



**Product code**  
5230

### Technical description

High output luminaire for general lighting designed to use LED lamps. Extruded aluminium component-holding box complete with plastic flow director designed to optimise light distribution. Polycarbonate safety screen as standard. Couplings for direct elect

### Installation

Ceiling- and wall-mounted.

### Dimension (mm)

598x26x38

### Colour

Aluminium (12)

### Mounting

wall surface|ceiling surface

### Wiring

product complete with electronic components

Complies with EN60598-1 and pertinent regulations



### Product configuration: 5230

### Product characteristics

Total lighting output [Lm]: 720  
Total power [W]: 10  
Luminous efficacy [Lm/W]: 72  
Life Time: 40,000h - L70 (Ta 25°C)


Total luminous flux at or above an angle of 90° [Lm]: 111  
Emergency luminous flux [Lm]: /  
Voltage [V]: -  
Number of optical assemblies: 1

### Optical assembly Characteristics Type 1

Light Output Ratio (L.O.R.) [%]: 100  
Lamp code: LED  
ZVEI Code: LED  
Nominal power [W]: 10  
Nominal luminous [Lm]: 720  
Lamp maximum intensity [cd]: /  
Beam angle [°]: /

Number of lamps for optical assembly: 1  
Socket: /  
Ballast losses [W]: 0  
Colour temperature [K]: 3000  
CRI: 80  
Wavelength [Nm]: /  
MacAdam Step: 4


### Polar



Utilisation factors

R	77	75	73	71	55	53	33	00	DRR
K0.8	58	47	39	33	44	37	35	27	32
1.0	64	53	46	40	50	43	41	32	38
1.5	74	65	58	52	61	54	51	42	50
2.0	80	72	66	60	68	62	59	49	58
2.5	84	77	71	66	72	67	64	54	64
3.0	86	80	75	71	75	71	67	58	69
4.0	90	85	81	77	80	76	72	63	74
5.0	92	88	84	81	83	79	75	66	78

Luminance curve limit



UGR diagram

Corrected UGR values (at 720 lm bare lamp luminous flux)											
Reflect.:		viewed crosswise					viewed endwise				
ceiling	cav	0.70	0.70	0.50	0.50	0.30	0.70	0.70	0.50	0.50	0.30
walls		0.50	0.30	0.50	0.30	0.30	0.50	0.30	0.50	0.30	0.30
work pl.		0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20
Room dim											
x	y										
2H	2H	19.8	20.9	20.4	21.5	22.1	19.1	20.2	19.7	20.8	21.4
	3H	22.0	23.0	22.6	23.6	24.3	19.7	20.7	20.3	21.2	21.9
	4H	23.1	24.1	23.7	24.7	25.3	19.9	20.9	20.5	21.5	22.1
	6H	24.2	25.1	24.8	25.7	26.4	20.1	21.0	20.7	21.6	22.3
	8H	24.8	25.6	25.4	26.2	26.9	20.2	21.0	20.8	21.7	22.4
	12H	25.3	26.1	25.9	26.7	27.4	20.2	21.0	20.8	21.6	22.3
4H	2H	20.5	21.4	21.1	22.0	22.7	21.2	22.1	21.8	22.7	23.4
	3H	22.9	23.7	23.5	24.4	25.1	22.0	22.8	22.6	23.4	24.1
	4H	24.2	24.9	24.8	25.6	26.3	22.4	23.2	23.1	23.8	24.5
	6H	25.5	26.1	26.1	26.8	27.6	22.9	23.5	23.5	24.2	25.0
	8H	26.1	26.7	26.8	27.4	28.2	23.1	23.7	23.7	24.3	25.1
	12H	26.7	27.3	27.4	28.0	28.8	23.2	23.8	23.9	24.4	25.2
8H	4H	24.5	25.1	25.2	25.8	26.6	23.2	23.8	23.8	24.4	25.2
	6H	26.1	26.6	26.8	27.3	28.1	23.8	24.4	24.5	25.1	25.9
	8H	26.8	27.3	27.6	28.0	28.9	24.2	24.7	24.9	25.4	26.2
	12H	27.7	28.1	28.4	28.8	29.6	24.6	25.0	25.3	25.8	26.6
12H	4H	24.6	25.1	25.2	25.8	26.6	23.3	23.8	24.0	24.5	25.3
	6H	26.2	26.6	26.9	27.3	28.2	24.0	24.5	24.7	25.2	26.0
	8H	27.0	27.4	27.8	28.2	29.0	24.5	24.9	25.2	25.6	26.5
Variations with the observer position at spacing:											
S =	1.0H	0.1 / -0.1					0.1 / -0.0				
	1.5H	0.2 / -0.2					0.2 / -0.2				
	2.0H	0.2 / -0.3					0.2 / -0.3				