

September 2012

**Ledplus -****Product code:**

B346

**Technical description:**

Luminaire designed to use RGB LEDs for signalling purposes that can be recessed, wall-mounted, applied to the floor or into a garden. It is made up of main body, closing glass, frame and outer casing (upon request). The large square body is made of high-resistance plastic material. The AISI 304-stainless-steel frame is 2.5 mm thick. It has two AISI 304-stainless-steel captive screws (used to anchor the body to the outer casing) and welded stud bolts. The outer casing used for installation must be ordered separately from the optical assembly. It is made of either painted cast aluminium (wall or floor application) or plastic material (garden installation). The optical assembly is closed at the top by a transparent hardened sodium-lime glass 10 mm thick and also has an internal opal screen. Black silicone rubber gaskets ensure perfect tightness. The body is fixed to the frame/glass unit by means of turned elements in stainless steel AISI 304. A stainless-steel cable clamp PG11 is used on the wiring system. The product comes complete with power supply cable L = 300 mm type H07RN-F 4x1 mm<sup>2</sup>. The power supply cable includes an anti-transpiration device. The unit made up of frame, glass, optical assembly and outer casing ensures resistance to 1000-kg static load (500 Kg in the version with plastic outer casing) in compliance with Standard EN60598-2-13. The LEDs are controlled by Colour Equalizer. Maximum glass surface temperature is lower than 40°C. All external screws are made of stainless steel AISI 304. Maximum absorbed power 5.2W

**Installation:**

Recessed application by means of an outer casing for embedding (to be ordered separately). The outer casing is available in the 100-mm painted cast-aluminium version complete with end cap (application to the wall or into the ground) or in the 150-mm plastic version (garden installation).

**Dimension:**

138x138 mm L=90 mm

**Colour:**

Steel (13)

**Weight [Kg]:**

0,9

**Mounting:**


Ground recessed|Wall recessed

**Wiring:**

Available ballasts: traditional, for DIN bar (1-10W, 20-30W, 60-120W), water-tight resin-coated. The product comes complete with an outgoing power-supply cord (L = 300 mm) H05RNF 2x1 mm<sup>2</sup> type and an electronic plate with LED 24V DC. Power supply to be ordered separately.

**Notes:**

Fitting complete with lamp. Monochromatic indicator LED available on request in colour white, blue, red, green and amber. Power supply to be ordered separately.



Complies with EN605981 and pertinent regulations

