


September 2012

**Linealuce - LED module with electronic control gear spot optic****Product code:**

B747

Technical description:

Luminaire designed to produce direct light with LED light sources and spot optic. The body is made of extruded aluminium EN1706AC 46100LF subjected to phosphochromatisation treatment with double primer and passivation at 120°C. The die-cast aluminium end caps are complete with silicone gaskets 50/60 Shore A and are subjected to post-cooling (oven) system 4/6 h at 200°C. The liquid acrylic paint is baked at 150°C and ensures high resistance to the external environment and UV rays. The top of the optical assembly is closed by a hardened transparent colourless soda-lime glass screen (4 mm thick) fixed by silicone and complete with a plate with power LED. Optic with lens in plastic material. The product comes equipped with a plastic-material translucent filter. Nickel-plated brass cable clamp PG11 for single entry of power supply cable. All external screws are made of stainless steel A2. Complete with lamp. Red, green and amber LED available upon request.

Installation:

Wall installation by means of brackets and arms that can be extended and adjusted $\pm 90^\circ$. Ceiling installation by means of plate for ceiling or surface application, suspension cables and rigid rods.

Dimension:

75 x 76mm L=638mm

Colour:

Grey (15)

Weight [Kg]:

2,4

Mounting:

Ceiling pendant|Ceiling surface|Wall surface

Wiring:

Electronic control gear inside the fitting 220 ÷ 240V 50 ÷ 60 Hz.

Notes:

Accessories available: antiglare screen and installation accessories.

Complies with EN605981 and pertinent regulations

