

Last information update: May 2018



**Pole-mounted system for urban and residential parks and gardens.**

**Product code**  
E223

#### Technical description

Outdoor luminaire with a symmetrical optic, designed to use LED lamps. Version with cut-off that eliminates skyward flux dispersion. The optical assembly and the pole attachment system are made of EN1706AC 46100LF aluminium alloy and subjected to a multi-step, pre-treatment process, in which the main phases are degreasing, fluorozirconation (a protective surface film) and sealing (with a nano-structured silane layer). The painting stage consists of a primer and a liquid acrylic paint, cured at 150 °C, with a high level of weather and UV ray resistance. Diffuser made of shockproof, UV-stabilised injection moulded polycarbonate. Complete with circuit fitted with monochrome LEDs. Optical assembly consisting of an anodized super-pure aluminium upper reflector, a methacrylate lens and a lower reflector made of metallised PC. Replaceable LEDs and driver. Electronic driver with Middle of the Night profile and automatic internal temperature control system. All external screws are made of stainless steel.

#### Installation

The spotlight can be installed with a pole-top mounting on poles with  $\varnothing$  60mm and 76mm end part using X102 and X126 accessories. Secured to the pole by two bolts.

#### Dimension (mm)

$\varnothing$ 650x202

#### Colour

Grey (15)

#### Weight (Kg)

4.89

#### Mounting

pole-top

#### Wiring

The product is supplied wired and with an outlet cable 1500mm long.

#### Notes

Oversvoltage protection: 5KV Common Mode, 5KV Differential Mode

Complies with EN60598-1 and pertinent regulations

IK10 IP66



#### Product configuration: E223

#### Product characteristics

Total lighting output [Lm]: 1940  
Total power [W]: 21.5  
Luminous efficacy [Lm/W]: 90.2  
Life Time: 59,000h - L90 - B10 (Ta 25°C)  
Life Time: 34,000h - L90 - B10 (Ta 40°C)  
Ambient temperature range: from -20°C to +35°C. (\*)

\* Preliminary data


Total luminous flux at or above an angle of 90° [Lm]: 0  
Emergency luminous flux [Lm]: /  
Voltage [V]: -  
Life Time: 100,000h - L80 - B10 (Ta 25°C)  
Life Time: 100,000h - L80 - B10 (Ta 40°C)  
Number of optical assemblies: 1

#### Optical assembly Characteristics Type 1

Light Output Ratio (L.O.R.) [%]: 100  
Lamp code: LED  
ZVEI Code: LED  
Nominal power [W]: /  
Nominal luminous [Lm]: /  
Lamp maximum intensity [cd]: /  
Beam angle [°]: /

Number of lamps for optical assembly: 1  
Socket: /  
Ballast losses [W]: 4.5  
Colour temperature [K]: 3000  
CRI: 80  
Wavelength [Nm]: /  
MacAdam Step: 2

**Polar**



**Isolux**

