


Last information update: May 2018

**Wall-mounted system with street optic.****Product code**  
E912**Technical description**

Outdoor luminaire with a street optic (ST1.C), designed to use LED lamps, supplied with a painted steel wall-mounted arm L=561mm. The optical assembly is made of EN1706AC 46100LF aluminium alloy and subjected to a multi-step, pre-treatment process, in which the main phases are degreasing, fluorozirconation (a protective surface film) and sealing (with a nano-structured silane layer). The painting stage consists of a primer and a liquid acrylic paint, cured at 150 °C, with a high level of weather and UV ray resistance. Diffusor made of shockproof, UV-stabilised injection moulded polycarbonate. Complete with circuit having monochrome LEDs and polymer optic multilayer lenses. Changeable driver and LEDs. Electronic driver with automatic Midnight recognition and an automatic internal temperature control system. All external screws are made of stainless steel.

**Installation**

Wall-mounted installation.

**Dimension (mm)**

Ø650

**Colour**

Grey (15)

**Weight (Kg)**

8.6

**Mounting**

wall arm|wall surface

**Wiring**

The product is supplied wired and with an outlet cable.

**Notes**

Overvoltage protection: 10KV Common Mode, 6KV Differential Mode

Complies with EN60598-1 and pertinent regulations

**Product configuration: E912****Product characteristics**

Total lighting output [Lm]: 3540  
 Total power [W]: 46  
 Luminous efficacy [Lm/W]: 77  
 Life Time: 100,000h - L90 - B10 (Ta 25°C)  
 Ambient temperature range: from -20°C to +35°C. (\*)

Total luminous flux at or above an angle of 90° [Lm]: 15  
 Emergency luminous flux [Lm]: /  
 Voltage [V]: -  
 Life Time: 100,000h - L80 - B10 (Ta 25°C)  
 Number of optical assemblies: 1


\* Preliminary data

**Optical assembly Characteristics Type 1**


Light Output Ratio (L.O.R.) [%]: 100  
 Lamp code: LED  
 ZVEI Code: LED  
 Nominal power [W]: /  
 Nominal luminous [Lm]: /  
 Lamp maximum intensity [cd]: /  
 Beam angle [°]: /

Number of lamps for optical assembly: 1  
 Socket: /  
 Ballast losses [W]: 5  
 Colour temperature [K]: 3000  
 CRI: 70  
 Wavelength [Nm]: /  
 MacAdam Step: 5

**Polar**



**Isolux**



**Utilisation factors**

