


Last information update: June 2018

**Mini47 – Wall-/Ceiling-mounted – TW – 48 Vdc DMX512-RDM – L=1205mm – Wall Grazing WideFlood optic****Product code**

EG42

**Technical description**

Direct light luminaire, designed to use TW LED lamps, DMX512-RDM 48Vdc dimmable with searching and addressing function. Ceiling-, wall- or surface-mounted. Consists of a body and supports for installation, to be ordered separately. The body is made of extruded aluminium and includes die-cast aluminium end caps with 50/60 Shore A silicone seals. It is subjected to a multi-step, pre-treatment process, in which the main phases are degreasing, fluorozirconation (a protective surface film) and sealing (with a nano-structured silane layer). The following painting stage consists of a primer and a liquid acrylic paint, cured at 150°C, with a high level of weather and UV ray resistance. The top of the optical assembly is closed by a 3 mm thick transparent glass screen, fixed with silicone. Complete with multi-LED plate in Tunable White and a 48V dc DMX512-RDM electronic driver (ballast to be ordered separately). Supplied with a double PG13.5 and outlet cables for pass-through wiring with IP68 male/female joiners. Fitted with a PMMA diffusing filter and optics with a plastic (methacrylate) lens for Wall Grazing WideFlood lighting. All external screws used are made of A2 stainless steel. The luminaire technical characteristics conform to EN 60598-1 standards and particular requirements.

**Installation**

Accessories are available for installation, like adjustable AISI304 stainless steel wall-mounted arms.

**Dimension (mm)**

1205x47x77

**Colour**

Grey (15)

**Mounting**

wall arm|wall surface|ceiling surface


**Wiring**

Complete with DMX-RDM 48-52Vdc control card. The product is supplied with a nickel-plated brass PG13.5 double cable gland with H07RN-F 5x1.5mm<sup>2</sup> rubber outlet cables for pass-through wiring with joiners (illegible part). Available for electrical connection and DMX-RDM control: IP68 5-pin female connector, IP68 5-pin male connector + closing cap (BZI6), and IP68 5-pin male + female connectors.

**Notes**

Product complete with LED lamp. DMX specifications require the insertion of a 120 Ohm terminating resistor to be placed between the DATA+ and DATA- cables of the last product in the line (BZQ7).

Complies with EN60598-1 and pertinent regulations

**Product characteristics**

Total lighting output [Lm]: 6830  
 Total power [W]: 52.1  
 Luminous efficacy [Lm/W]: 131.09  
 Ambient temperature range: from -20°C to +35°C. (\*)

Total luminous flux at or above an angle of 90° [Lm]: 0  
 Emergency luminous flux [Lm]: /  
 Voltage [V]: -  
 Number of optical assemblies: 1

\* Preliminary data

**Optical assembly Characteristics Type 1**

Light Output Ratio (L.O.R.) [%]: /  
 Lamp code: /  
 ZVEI Code: LED  
 Nominal power [W]: 52.1  
 Nominal luminous [Lm]: 6830  
 Lamp maximum intensity [cd]: /  
 Beam angle [°]: 15° / 53°

Number of lamps for optical assembly: 1  
 Socket: /  
 Ballast losses [W]: /  
 Colour temperature [K]: None  
 CRI: 80  
 Wavelength [Nm]: /  
 MacAdam Step: /