


Last information update: June 2018

**Spotlight with base - Warm White Led - integrated electronic control gear - Super Spot optic****Product code**

EH87

Technical description

Spotlight designed to use LED lamps and a Super Spot optic. The optical assembly and base is made of EN1706AC 46100LF aluminium alloy and subjected to a multi-step, pre-treatment process, in which the main phases are degreasing, fluorozirconation (a protective surface film) and sealing (with a nano-structured silane layer). The following painting stage consists of a primer and a liquid acrylic paint, cured at 150°C, with a high level of weather and UV ray resistance. 5 mm thick tempered sodium-calcium closing glass. Double adjustability allows a 360° rotation about the vertical axis and 90° tilting relative to the horizontal plane. Mechanical aiming locks for rotation on both the vertical axis and horizontal plane. Complete with a monochrome LED circuit and an Opti Beam Lens optic system. The product includes a PG13.5 cable gland. Electronic On/Off ballast integrated in product. Option of using optic accessories assembled via an accessory holder frame. All external screws used are made of A2 stainless steel.

Installation

Floor, wall, ceiling or ground-installed via pole or stake.

Dimension (mm)

Ø83

Colour

White (01) | Grey (15)

Weight (Kg)

1.9


Mounting

wall surface|ground spike

Wiring

Double PG.

Complies with EN60598-1 and pertinent regulations

**Product configuration: EH87****Product characteristics**

Total lighting output [Lm]: 600
Total power [W]: 10.9
Luminous efficacy [Lm/W]: 55
Life Time: 70,000h - L80 - B10 (Ta 25°C)
Ambient temperature range: from -20°C to +35°C. (*)

* Preliminary data


Total luminous flux at or above an angle of 90° [Lm]: 0
Emergency luminous flux [Lm]: /
Voltage [V]: -
Life Time: 70,000h - L80 - B10 (Ta 40°C)
Number of optical assemblies: 1

Optical assembly Characteristics Type 1


Light Output Ratio (L.O.R.) [%]: 75
Lamp code: LED
ZVEI Code: LED
Nominal power [W]: 9.1
Nominal luminous [Lm]: 800
Lamp maximum intensity [cd]: /
Beam angle [°]: 8°

Number of lamps for optical assembly: 1
Socket: /
Ballast losses [W]: 1.8
Colour temperature [K]: 2700
CRI: 80
Wavelength [Nm]: /
MacAdam Step: 3

Polar



Isolux



UGR diagram

Corrected UGR values (at 800 lm bare lamp luminous flux)											
Reflect.: ceiling/cav walls work pl. Room dim x y		0.70 0.50 0.20	0.70 0.30 0.20	0.50 0.50 0.20	0.50 0.30 0.20	0.30 0.30 0.20	0.70 0.50 0.20	0.70 0.30 0.20	0.50 0.50 0.20	0.50 0.30 0.20	0.30 0.30 0.20
viewed crosswise						viewed endwise					
2H	2H	7.2	9.2	7.6	9.5	9.8	7.2	9.2	7.6	9.5	9.8
	3H	7.1	8.4	7.5	8.7	9.0	7.1	8.4	7.5	8.7	9.0
	4H	7.1	8.0	7.4	8.3	8.7	7.1	8.1	7.5	8.4	8.7
	6H	7.0	7.7	7.4	8.1	8.4	7.1	7.8	7.4	8.1	8.4
	8H	7.0	7.8	7.3	8.1	8.4	7.0	7.8	7.4	8.1	8.5
	12H	6.9	7.8	7.3	8.1	8.5	6.9	7.8	7.3	8.2	8.5
4H	2H	7.1	8.1	7.5	8.4	8.7	7.1	8.0	7.4	8.3	8.7
	3H	6.9	7.8	7.3	8.2	8.6	6.9	7.8	7.3	8.2	8.6
	4H	6.7	7.9	7.1	8.3	8.7	6.7	7.9	7.1	8.3	8.7
	6H	6.4	8.1	6.9	8.6	9.0	6.4	8.1	6.9	8.6	9.0
	8H	6.3	8.1	6.8	8.6	9.1	6.3	8.1	6.8	8.6	9.1
	12H	6.2	8.1	6.7	8.5	9.1	6.2	8.1	6.7	8.5	9.1
8H	4H	6.3	8.1	6.8	8.6	9.1	6.3	8.1	6.8	8.6	9.1
	6H	6.2	7.8	6.7	8.3	8.8	6.2	7.8	6.7	8.3	8.8
	8H	6.3	7.5	6.8	8.0	8.5	6.3	7.5	6.8	8.0	8.5
	12H	6.4	7.1	6.9	7.6	8.1	6.4	7.1	6.9	7.6	8.1
12H	4H	6.2	8.1	6.7	8.5	9.1	6.2	8.1	6.7	8.5	9.1
	6H	6.3	7.5	6.8	8.0	8.5	6.3	7.5	6.8	8.0	8.5
	8H	6.4	7.1	6.9	7.6	8.1	6.4	7.1	6.9	7.6	8.1
Variations with the observer position at spacing:											
S =	1.0H	4.9 / -7.6					4.9 / -7.6				
	1.5H	7.6 / -11.6					7.6 / -11.6				
	2.0H	9.6 / -16.8					9.6 / -16.8				