


Last information update: June 2018




---

**module for continuous line L=1197 - Low Contrast - direct emission - LED - neutral white integrated electronic control gear**


---

**Product code**

ME40

**Technical description**

direct emission modular lighting system with LED lamps. Module for general lighting (Low Contrast) specifically for continuous line. Minimal (frameless) version extruded aluminium single length profile; methacrylate opal screen set up for connection to other modules by overlapping; mechanical systems for connection between modules included in the package. Installation can be recessed, surface-mounted (ceiling/wall), or pendant. The module must be completed with the accessories kit needed for the selected type of installation. Electronic control gear integrated in the luminaire. Neutral white high efficiency LED.

**Installation**

pendant: complete with power supply unit with cable (MWG5) and suspension cables (MWG6); surface-mounted: complete with supports (MWG7); recessed: after making the preparation slot, use the special supports to install in the false ceiling (MWG8).

**Dimension (mm)**

1197x32x75

**Colour**

Aluminium (12)

**Weight (Kg)**

2.13

**Mounting**

ceiling recessed|ceiling surface|ceiling pendant

**Wiring**

the module is fitted with 5-pin terminal blocks for pass-through wiring at the ends; the accessory power supply unit code MWG5 has a fixing plate with 5-pin terminal block for connection to the main power supply. Electronic control gear integrated in the module.

**Notes**

the intermediate modules are specifically for continuous line installation. To correctly complete a continuous line, always use an initial module at the start or end of the structure. Possibility of combined Low Contrast / High Contrast.

Complies with EN60598-1 and pertinent regulations



IP20

**Product configuration: ME40****Product characteristics**

Total lighting output [Lm]: 2032  
 Total power [W]: 22.6  
 Luminous efficacy [Lm/W]: 89.9  
 Life Time: 50,000h - L80 - B10 (Ta 25°C)


Total luminous flux at or above an angle of 90° [Lm]: 0.4  
 Emergency luminous flux [Lm]: /  
 Voltage [V]: -  
 Number of optical assemblies: 1

**Optical assembly Characteristics Type 1**

Light Output Ratio (L.O.R.) [%]: 77  
 Lamp code: LED  
 ZVEI Code: LED  
 Nominal power [W]: 17  
 Nominal luminous [Lm]: 2650  
 Lamp maximum intensity [cd]: /  
 Beam angle [°]: /

Number of lamps for optical assembly: 1  
 Socket: /  
 Ballast losses [W]: 5.6  
 Colour temperature [K]: 4000  
 CRI: 80  
 Wavelength [Nm]: /  
 MacAdam Step: 3

**Polar**



**Utilisation factors**

R	77	75	73	71	55	53	33	00	DRR
K0.8	50	42	36	32	41	36	35	30	39
1.0	55	48	42	38	46	41	41	35	46
1.5	63	57	52	48	55	51	50	45	59
2.0	68	63	58	55	61	57	56	52	67
2.5	71	66	63	60	65	61	60	56	73
3.0	73	69	66	63	67	64	63	59	77
4.0	75	72	70	67	70	68	67	63	82
5.0	77	74	72	70	72	70	69	66	85

**Luminance curve limit**

