

Last information update: June 2018



rectangular recessed luminaire with 3 optical assemblies - neutral white passive dissipation LEDs - integrated electronic control gear - wide flood

**Product code**  
MF21

#### Technical description

Multiple recessed adjustable removable luminaire for LED lamp with passive heat dissipation system. Sheet steel perimeter frame. Main structure made of die-cast aluminium. Steel rotation hinges. Die-cast aluminium lamp bodies with shaped surface for high level radiant effect for effectively reducing the temperature and keeping the long-term LED lamp performance unchanged. Chrome-plated aluminium lamp body closing rings. Reflectors with high efficiency super-pure aluminium optic - wide flood beam angle. Bodies adjusted using manually operated device: internal 29° - external 75° - rotation about axis 355°. During adjustment and rotation the lamp bodies are subject to some limitations. Consult the instruction sheet. Supplied with electronic control gear units connected to the luminaire. Neutral white high efficiency LED.

#### Installation

recessed: preparation slot 138 x 386 mm; perimeter frame preliminary fixing on false ceiling (min. thickness 1 mm) with adjustable metal brackets; main structure inserted and mechanically locked on the frame

#### Dimension (mm)

398x151x109

#### Colour

White/Aluminium (39) | Grey/Black/Aluminium (E1)

#### Weight (Kg)

3.5

#### Mounting

ceiling recessed

#### Wiring

on control gear box with quick-coupling connections; each lamp body has a specific ballast, allowing separate switch ons

#### Notes

the configuration of the lamp bodies causes some limitations during angling and rotation; consult the instruction leaflet

Complies with EN60598-1 and pertinent regulations



IP20



#### Product configuration: MF21

#### Product characteristics

Total lighting output [Lm]: 4676  
Total power [W]: 46.2  
Luminous efficacy [Lm/W]: 101.2  
Life Time: > 50,000h - L80 - B10 (Ta 25°C)


Total luminous flux at or above an angle of 90° [Lm]: 0  
Emergency luminous flux [Lm]: /  
Voltage [V]: -  
Number of optical assemblies: 3

#### Optical assembly Characteristics Type 1

Light Output Ratio (L.O.R.) [%]: 78  
Lamp code: LED  
ZVEI Code: LED  
Nominal power [W]: 12  
Nominal luminous [Lm]: 2000  
Lamp maximum intensity [cd]: /  
Beam angle [°]: 54°

Number of lamps for optical assembly: 1  
Socket: /  
Ballast losses [W]: 3.4  
Colour temperature [K]: 4000  
CRI: 80  
Wavelength [nm]: /  
MacAdam Step: 2

# Polar



# UGR diagram

Corrected UGR values (at 2000 lm bare lamp luminous flux)												
Reflect.: ceiling/cav walls work pl. Room dim x y		0.70	0.70	0.50	0.50	0.30	0.70	0.70	0.50	0.50	0.30	0.30
		0.50	0.30	0.50	0.30	0.30	0.50	0.30	0.50	0.30	0.30	0.30
		0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20
		viewed crosswise					viewed endwise					
2H	2H	15.6	16.2	15.8	16.4	16.7	15.6	16.2	15.8	16.4	16.7	
	3H	15.4	16.0	15.7	16.3	16.5	15.4	16.0	15.7	16.3	16.5	
	4H	15.4	15.9	15.7	16.2	16.5	15.4	15.9	15.7	16.2	16.5	
	6H	15.3	15.8	15.6	16.1	16.4	15.3	15.8	15.6	16.1	16.4	
	8H	15.2	15.7	15.6	16.0	16.4	15.2	15.7	15.6	16.0	16.4	
	12H	15.2	15.6	15.6	16.0	16.3	15.2	15.6	15.6	16.0	16.3	
4H	2H	15.4	15.9	15.7	16.2	16.5	15.4	15.9	15.7	16.2	16.5	
	3H	15.2	15.7	15.6	16.0	16.3	15.2	15.7	15.6	16.0	16.3	
	4H	15.1	15.5	15.5	15.9	16.3	15.1	15.5	15.5	15.9	16.3	
	6H	15.0	15.4	15.5	15.8	16.2	15.0	15.4	15.5	15.8	16.2	
	8H	15.0	15.3	15.4	15.7	16.2	15.0	15.3	15.4	15.7	16.2	
	12H	14.9	15.2	15.4	15.7	16.1	14.9	15.2	15.4	15.7	16.1	
8H	4H	15.0	15.3	15.4	15.7	16.2	15.0	15.3	15.4	15.7	16.2	
	6H	14.9	15.2	15.4	15.6	16.1	14.9	15.2	15.4	15.6	16.1	
	8H	14.9	15.1	15.3	15.5	16.0	14.9	15.1	15.3	15.5	16.0	
	12H	14.8	15.0	15.3	15.5	16.0	14.8	15.0	15.3	15.5	16.0	
12H	4H	14.9	15.2	15.4	15.7	16.1	14.9	15.2	15.4	15.7	16.1	
	6H	14.8	15.1	15.3	15.5	16.0	14.9	15.1	15.3	15.5	16.0	
	8H	14.8	15.0	15.3	15.5	16.0	14.8	15.0	15.3	15.5	16.0	
Variations with the observer position at spacing:												
S =		1.0H	5.1 / -13.5					5.1 / -13.5				
		1.5H	7.9 / -14.7					7.9 / -14.7				
		2.0H	9.9 / -15.9					9.9 / -15.9				