


Last information update: June 2018

**15 - cell Recessed luminaire - LED - Neutral white Flood optic****Product code**

MK55

Technical description

rectangular miniaturised recessed luminaire with 15 optical elements with LED lamps - fixed optics - flood beam angle. Main body with die-cast aluminium radiant surface, version with perimeter surface frame. Metallised thermoplastic high definition optics, integrated in a rear position in the black anti-glare screen; the structure of the optical system prevents a pinpoint effect, allowing precise, circular light distribution and emission with controlled glare. Supplied with DALI dimmable electronic control gear connected to the luminaire. Neutral white LED.

Installation

recessed with steel wire springs for false ceilings from 1 to 25 mm thick - preparation hole 37 x 406

Dimension (mm)

413x44x54

Colour

White (01) | Black/Black (43) | Black/White (47) | Grey/Black (74)

Weight (Kg)

0.86

Mounting

wall recessed|ceiling recessed

Wiring

on control gear box with quick-coupling connections

Complies with EN60598-1 and pertinent regulations



IP20

IP23

On the visible part of the product once installed

**Product configuration: MK55****Product characteristics**


Total lighting output [Lm]: 2289
Total power [W]: 35
Luminous efficacy [Lm/W]: 65.4
Life Time: 50,000h - L90 - B10 (Ta 25°C)

Total luminous flux at or above an angle of 90° [Lm]: 0
Emergency luminous flux [Lm]: /
Voltage [V]: -
Number of optical assemblies: 1

Optical assembly Characteristics Type 1

Light Output Ratio (L.O.R.) [%]: 83
Lamp code: LED
ZVEI Code: LED
Nominal power [W]: 31
Nominal luminous [Lm]: 2760
Lamp maximum intensity [cd]: /
Beam angle [°]: 48°

Number of lamps for optical assembly: 1
Socket: /
Ballast losses [W]: 4
Colour temperature [K]: 4000
CRI: 95
Wavelength [nm]: /
MacAdam Step: 3

Polar

Utilisation factors

R	77	75	73	71	55	53	33	00	DRR
K0.8	75	71	68	66	70	68	68	65	78
1.0	78	75	72	70	74	72	71	69	83
1.5	82	79	77	76	79	77	76	74	89
2.0	85	83	81	80	82	80	79	77	93
2.5	86	85	84	83	84	83	82	79	96
3.0	87	86	85	85	85	84	83	81	98
4.0	88	87	87	86	86	86	84	82	99
5.0	89	88	88	88	87	86	85	83	100

UGR diagram

Corrected UGR values (at 2760 lm bare lamp luminous flux)											
Reflect.: ceiling/cav walls work pl. Room dim x y		0.70	0.70	0.50	0.50	0.30	0.70	0.70	0.50	0.50	0.30
		0.50	0.30	0.50	0.30	0.30	0.50	0.30	0.50	0.30	0.30
		0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20
		viewed crosswise					viewed endwise				
2H	2H	1.4	1.9	1.7	2.1	2.4	1.4	1.9	1.7	2.1	2.4
	3H	1.3	1.7	1.6	2.0	2.3	1.3	1.7	1.6	2.0	2.3
	4H	1.2	1.7	1.6	1.9	2.2	1.2	1.7	1.6	1.9	2.2
	6H	1.2	1.5	1.5	1.9	2.2	1.2	1.5	1.5	1.9	2.2
	8H	1.1	1.5	1.5	1.8	2.2	1.1	1.5	1.5	1.8	2.1
	12H	1.1	1.4	1.5	1.8	2.1	1.1	1.4	1.5	1.8	2.1
4H	2H	1.2	1.7	1.6	1.9	2.2	1.2	1.7	1.6	1.9	2.2
	3H	1.1	1.4	1.5	1.8	2.1	1.1	1.4	1.5	1.8	2.1
	4H	1.0	1.3	1.4	1.7	2.1	1.0	1.3	1.4	1.7	2.1
	6H	0.9	1.2	1.3	1.6	2.0	0.9	1.2	1.3	1.6	2.0
	8H	0.9	1.1	1.3	1.5	2.0	0.9	1.1	1.3	1.5	2.0
	12H	0.8	1.0	1.3	1.5	1.9	0.8	1.0	1.3	1.5	1.9
8H	4H	0.9	1.1	1.3	1.5	2.0	0.9	1.1	1.3	1.5	2.0
	6H	0.8	1.0	1.2	1.4	1.9	0.8	1.0	1.2	1.4	1.9
	8H	0.7	0.9	1.2	1.4	1.9	0.7	0.9	1.2	1.4	1.9
	12H	0.7	0.8	1.2	1.3	1.8	0.7	0.8	1.2	1.3	1.8
12H	4H	0.8	1.0	1.3	1.5	1.9	0.8	1.0	1.3	1.5	1.9
	6H	0.7	0.9	1.2	1.4	1.9	0.7	0.9	1.2	1.4	1.9
	8H	0.7	0.8	1.2	1.3	1.8	0.7	0.8	1.2	1.3	1.8
Variations with the observer position at spacing:											
S =		1.0H	6.9 / -18.0					6.9 / -18.0			
		1.5H	9.7 / -18.3					9.7 / -18.3			
		2.0H	11.7 / -18.4					11.7 / -18.4			