Design iGuzzini

iGuzzini

Last information update: May 2018



15 - cell Frameless Recessed luminaire - LED - Warm white - Incorporated DALI dimmable power supply - Wide Flood optic

Product code

MM90

Technical description

rectangular miniaturised recessed luminaire with 15 optical elements with LED lamps - fixed optics - wide flood beam angle. Main body with die-cast aluminium radiant surface, minimal (frameless) version for mounting flush with the ceiling. Metallised thermoplastic high definition optics, integrated in a rear position in the black anti-glare screen; the structure of the optical system prevents a pinpoint effect, allowing precise, circular light distribution and emission with controlled glare . Supplied with DALI dimmable electronic control gear connected to the luminaire. Warm white high colour rendering LED





404x35

Installation

recessed with steel wire springs on the specific adapter (included) which allows flush-mounting with the ceiling. Adapter fixed to false ceiling (12.5 mm thick) with self-tapping screws; subsequent filling and smoothing operations; insertion of luminaire body and aesthetic finishing. Preparation hole 35 x 403

Dimension (mm)

396x30x56

Colour

White (01) | Black (04)

Weight (Kg)

Mounting

wall recessed|ceiling recessed

Wiring

on control gear box with quick-coupling connections

Complies with EN60598-1 and pertinent regulations









A++









Product configuration: MM90

Product characteristics

Total lighting output [Lm]: 2114.7

Total power [W]: 35

Luminous efficacy [Lm/W]: 60.4 Life Time: 50,000h - L90 - B10 (Ta 25°C)

Emergency luminous flux [Lm]: / Voltage [V]: Number of optical assemblies: 1

Optical assembly Characteristics Type 1

Light Output Ratio (L.O.R.) [%]: 83

Lamp code: LED ZVEI Code: LED Nominal power [W]: 31 Nominal luminous [Lm]: 2550 Lamp maximum intensity [cd]: / Beam angle [°]: 48°

Number of lamps for optical assembly: 1

Total luminous flux at or above an angle of 90° [Lm]: 0

Socket: / Ballast losses [W]: 4

Colour temperature [K]: 2700

CRI: 95 Wavelength [Nm]: /

MacAdam Step: 3

Polar



