
Design Renzo Piano

iGuzzini

Large body spotlight - warm white - electronic ballast - medium optic

Last information update: June 2018



## Product code MQ03

### Technical description

Pendant luminaire equipped with a multiphase adapter made of die-cast aluminium and thermoplastic material. The pendant system consists of steel cables L=2000 that provide a simple mechanical anchoring system. Having been rotated and tilted, the luminaire can be locked mechanically in position to ensure efficient light aiming (even during maintenance operations). Luminaire for high output LED lamp with monochrome emission in a warm white colour tone (3000K). Electronic ballast. Equipped with an accessory holding ring designed to contain a flat accessory. Another external component can also be applied, selected from directional flaps and an asymmetric screen. All external accessories rotate 360° about the spotlight longitudinal axis.

### Installation

Mounted on an electrified track with a multiphase adapter.

Dimension (mm) Ø162x300

## **Colour** White (01) | Grey/Black (74)

Weight (Kg) 3.1

Mounting ceiling pendant

# Wiring

Electronic components housed in the luminaire.



## Product configuration: MQ03

## Product characteristics

Total lighting output [Lm]: 3244Total luminoTotal power [W]: 37.5EmergencyLuminous efficacy [Lm/W]: 86.5Voltage [V]Life Time: > 50,000h - L80 - B10 (Ta 25°C)Number of a

## Optical assembly Characteristics Type 1

Light Output Ratio (L.O.R.) [%]: 74 Lamp code: LED ZVEI Code: LED Nominal power [W]: 33 Nominal luminous [Lm]: 4400 Lamp maximum intensity [cd]: / Beam angle [°]: 16° Total luminous flux at or above an angle of 90  $^{\circ}$  [Lm]: 0 Emergency luminous flux [Lm]: / Voltage [V]: - Number of optical assemblies: 1

Complies with EN60598-1 and pertinent regulations

Number of lamps for optical assembly: 1 Socket: / Ballast losses [W]: 4.5 Colour temperature [K]: 3000 CRI: 90 Wavelength [Nm]: / MacAdam Step: 2

