

Laser Blade

Design iGuzzini

iGuzzini

Last information update: May 2018



Adjustable 2 x 10 - cell Recessed frame - LED - Warm white - Incorporated DALI dimmable power supply - Beam 48°

Product code

MQ36

Technical description

Recessed rectangular luminaire with LEDs. Shaped steel sheet structural compartment with outer rim. The two linear elements with 10 lighting cells, in die-cast aluminium and independently adjustable, can be used to direct the emission with a tilting adjustability of +/- 30°. Metallised thermoplastic high definition optics, integrated in a rear position in the black anti-glare screen; the structure of the optical system prevents a pinpoint effect, allowing precise, circular light distribution and emission with controlled glare. Supplied with DALI dimmable control gear connected to the luminaire. Warm white high chromatic yield LED.

Installation

recessed with mechanical blocking system for false ceilings from 1 to 25 mm; can be installed on ceilings and walls (vertical + horizontal) - preparation slot 135 x 295

Dimension (mm)

302x142x89

Colour

Black/Black (43) | Black/White (47) | Grey/Black (74)

Weight (Kg)

2.8

Mounting

wall recessed|ceiling recessed

Wiring

on power box: screw connections

Notes

dimming function with pushbutton (TOUCH DIM/PUSH): for this option consult the instructions included in the package

Complies with EN60598-1 and pertinent regulations



IP20



Product configuration: MQ36

Product characteristics



Total lighting output [Lm]: 2819.6
Total power [W]: 46.5
Luminous efficacy [Lm/W]: 60.6
Life Time: 50,000h - L90 - B10 (Ta 25°C)

Total luminous flux at or above an angle of 90° [Lm]: 0
Emergency luminous flux [Lm]: /
Voltage [V]: -
Number of optical assemblies: 2

Optical assembly Characteristics Type 1

Light Output Ratio (L.O.R.) [%]: 83
Lamp code: LED
ZVEI Code: LED
Nominal power [W]: 21
Nominal luminous [Lm]: 1700
Lamp maximum intensity [cd]: /
Beam angle [°]: 48°

Number of lamps for optical assembly: 1
Socket: /
Ballast losses [W]: 2.3
Colour temperature [K]: 3000
CRI: 95
Wavelength [Nm]: /
MacAdam Step: 3



295x135

Polar

	Imax=2497 cd 90° 180° 90° 2500 0° α=48°	CIE nL 0.83 100-100-100-100-83 UGR <10-<10 DIN A.61 UTE 0.83A+0.00T F*1=999 F*1+F*2=1000 F*1+F*2+F*3=1000 CIBSE LG3 L<200 cd/m² at 65° BZ1	Lux h d Em Emax 2 1.8 523 623 4 3.6 131 156 6 5.3 58 69 8 7.1 33 39
--	--	---	---

Utilisation factors

R	77	75	73	71	55	53	33	00	DRR
K0.8	75	71	68	66	70	68	68	65	78
1.0	78	75	72	70	74	72	71	69	83
1.5	82	79	77	76	79	77	76	74	89
2.0	85	83	81	80	82	80	79	77	93
2.5	86	85	84	83	84	83	82	79	96
3.0	87	86	85	85	85	84	83	81	98
4.0	88	87	87	86	86	86	84	82	99
5.0	89	88	88	88	87	86	85	83	100

UGR diagram

Corrected UGR values (at 1700 lm bare lamp luminous flux)											
Reflect.:		viewed crosswise					viewed endwise				
ceiling/cav		0.70	0.70	0.50	0.50	0.30	0.70	0.70	0.50	0.50	0.30
walls		0.50	0.30	0.50	0.30	0.30	0.50	0.30	0.50	0.30	0.30
work pl.		0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20
Room dim											
x	y										
2H	2H	1.1	1.6	1.4	1.8	2.0	1.1	1.6	1.4	1.8	2.0
	3H	1.0	1.4	1.3	1.7	1.9	1.0	1.4	1.3	1.7	1.9
	4H	0.9	1.3	1.2	1.6	1.9	0.9	1.3	1.2	1.6	1.9
	6H	0.8	1.2	1.2	1.5	1.8	0.8	1.2	1.2	1.5	1.8
	8H	0.8	1.2	1.2	1.5	1.8	0.8	1.2	1.1	1.5	1.8
12H	0.8	1.1	1.1	1.4	1.8	0.8	1.1	1.1	1.4	1.8	
4H	2H	0.9	1.3	1.2	1.6	1.9	0.9	1.3	1.2	1.6	1.9
	3H	0.8	1.1	1.1	1.4	1.8	0.8	1.1	1.1	1.4	1.8
	4H	0.7	1.0	1.1	1.3	1.7	0.7	1.0	1.1	1.3	1.7
	6H	0.6	0.8	1.0	1.2	1.7	0.6	0.8	1.0	1.2	1.7
	8H	0.5	0.8	1.0	1.2	1.6	0.5	0.8	1.0	1.2	1.6
12H	0.5	0.7	0.9	1.1	1.6	0.5	0.7	0.9	1.1	1.6	
8H	4H	0.5	0.8	1.0	1.2	1.6	0.5	0.8	1.0	1.2	1.6
	6H	0.4	0.6	0.9	1.1	1.6	0.4	0.6	0.9	1.1	1.6
	8H	0.4	0.6	0.9	1.0	1.5	0.4	0.6	0.9	1.0	1.5
	12H	0.3	0.5	0.8	1.0	1.5	0.3	0.5	0.8	1.0	1.5
12H	4H	0.5	0.7	0.9	1.1	1.6	0.5	0.7	0.9	1.1	1.6
	6H	0.4	0.6	0.9	1.0	1.5	0.4	0.6	0.9	1.0	1.5
	8H	0.3	0.5	0.8	1.0	1.5	0.3	0.5	0.8	1.0	1.5
Variations with the observer position at spacing:											
S =	1.0H	6.9 / -18.0					6.9 / -18.0				
	1.5H	9.7 / -18.3					9.7 / -18.3				
	2.0H	11.7 / -18.4					11.7 / -18.4				