


Last information update: May 2018

**596 X 596 mm - warm white LED - electronic control gear - general light optic opaline screen****Product code**

MT11

Technical description


Direct emission recessed or ceiling-mounted luminaire (with accessories ordered separately) designed to use warm white 3,000K high colour rendering LEDs. The optical assembly consists of a white extruded frame, a satin methacrylate diffuser screen for general light emission and a sheet metal rear closing base. The LEDs are arranged inside the perimeter and the driver is housed in the upper part of the product.

Installation

Recessed in plasterboard false ceilings (using accessory frame), in false ceilings with frame, in modular false ceilings (even 625 x 625 mm using accessory adapter); possibility of ceiling-mounting using kit to be ordered separately as an accessory

Dimension (mm)

596x596x14

**Colour**

White (01)

Weight (Kg)

6

Mounting

ceiling recessed|wall surface|ceiling surface

Wiring

product complete with electronic components

Complies with EN60598-1 and pertinent regulations

**Product configuration: MT11****Product characteristics**

Total lighting output [Lm]: 3439.6
 Total power [W]: 30.9
 Luminous efficacy [Lm/W]: 111.3
 Life Time: 50,000h - L80 - B10 (Ta 25°C)


Total luminous flux at or above an angle of 90° [Lm]: 0
 Emergency luminous flux [Lm]: /
 Voltage [V]: -
 Number of optical assemblies: 1

Optical assembly Characteristics Type 1

Light Output Ratio (L.O.R.) [%]: 80
 Lamp code: LED
 ZVEI Code: LED
 Nominal power [W]: 26
 Nominal luminous [Lm]: 4300
 Lamp maximum intensity [cd]: /
 Beam angle [°]: /

Number of lamps for optical assembly: 1
 Socket: /
 Ballast losses [W]: 4.9
 Colour temperature [K]: 3000
 CRI: 80
 Wavelength [Nm]: /
 MacAdam Step: 3


Polar



Utilisation factors

R	77	75	73	71	55	53	33	00	DRR
K0.8	52	44	38	33	43	37	37	31	39
1.0	58	50	44	39	48	43	43	37	46
1.5	66	59	54	50	58	53	53	47	59
2.0	71	66	61	58	64	60	59	54	68
2.5	74	69	66	63	68	65	63	59	74
3.0	76	72	69	66	70	68	66	62	78
4.0	79	75	73	70	74	72	70	66	83
5.0	80	78	75	73	76	74	72	69	86

Luminance curve limit



UGR diagram

Corrected UGR values (at 4300 lm bare lamp luminous flux)											
Reflect.:											
ceiling/cav		0.70	0.70	0.50	0.50	0.30	0.70	0.70	0.50	0.50	0.30
walls		0.50	0.30	0.50	0.30	0.30	0.50	0.30	0.50	0.30	0.30
work pl.		0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20
Room dim		viewed					viewed				
x	y	crosswise					endwise				
2H	2H	17.2	18.4	17.5	18.6	18.9	17.2	18.4	17.5	18.6	18.9
	3H	18.7	19.8	19.1	20.1	20.4	17.7	18.8	18.0	19.1	19.4
	4H	19.3	20.4	19.7	20.7	21.0	17.8	18.9	18.2	19.2	19.5
	6H	19.8	20.8	20.2	21.1	21.4	17.9	18.9	18.3	19.2	19.6
	8H	20.0	20.9	20.3	21.2	21.6	17.9	18.9	18.3	19.2	19.6
	12H	20.1	20.9	20.5	21.3	21.7	17.9	18.8	18.3	19.2	19.5
4H	2H	17.8	18.9	18.2	19.2	19.5	19.3	20.4	19.7	20.7	21.0
	3H	19.6	20.5	20.0	20.8	21.2	20.0	20.9	20.4	21.3	21.6
	4H	20.3	21.1	20.7	21.5	21.9	20.3	21.1	20.7	21.5	21.9
	6H	20.9	21.6	21.3	22.0	22.4	20.5	21.2	21.0	21.6	22.1
	8H	21.1	21.7	21.6	22.2	22.6	20.6	21.2	21.1	21.7	22.1
	12H	21.2	21.8	21.7	22.3	22.7	20.6	21.2	21.1	21.6	22.1
8H	4H	20.6	21.2	21.1	21.7	22.1	21.1	21.7	21.6	22.2	22.6
	6H	21.3	21.9	21.8	22.3	22.8	21.5	22.0	21.9	22.4	22.9
	8H	21.6	22.1	22.1	22.5	23.0	21.6	22.1	22.1	22.5	23.0
	12H	21.8	22.2	22.3	22.7	23.2	21.7	22.1	22.2	22.6	23.1
12H	4H	20.6	21.2	21.1	21.6	22.1	21.2	21.8	21.7	22.3	22.7
	6H	21.4	21.8	21.9	22.3	22.8	21.6	22.1	22.1	22.6	23.1
	8H	21.7	22.1	22.2	22.6	23.1	21.8	22.2	22.3	22.7	23.2
Variations with the observer position at spacing:											
S =	1.0H	0.1 / -0.1					0.1 / -0.1				
	1.5H	0.3 / -0.3					0.3 / -0.3				
	2.0H	0.4 / -0.5					0.4 / -0.5				