

Last information update: May 2018



596 X 596 mm - warm white LED - DALI control gear - controlled luminance optic UGR<19

Product code

MT17

Technical description

Direct emission recessed or ceiling-mounted luminaire (with accessories ordered separately) designed to use warm white 3,000K high colour rendering LEDs. The optical assembly consists of a white extruded frame, a satin methacrylate diffuser screen for controlled luminance UGR<19 emission and a sheet metal rear closing base. The LEDs are arranged inside the perimeter and the electronic driver is housed in the upper part of the product.

Installation

Recessed in plasterboard false ceilings (using accessory frame), in false ceilings with frame, in modular false ceilings (even 625 x 625 mm using accessory adapter); possibility of ceiling-mounting using kit to be ordered separately as an accessory

Dimension (mm)

596x596x14

Colour

White (01)

Weight (Kg)

6

Mounting

ceiling recessed|wall surface|ceiling surface

Wiring

product complete with DALI components

Complies with EN60598-1 and pertinent regulations



IP20



IP43

On the visible part of the product once installed

**Product configuration: MT17****Product characteristics**

Total lighting output [Lm]: 3439.6
Total power [W]: 30.4
Luminous efficacy [Lm/W]: 113.1
Life Time: 50,000h - L80 - B10 (Ta 25°C)

Total luminous flux at or above an angle of 90° [Lm]: 0
Emergency luminous flux [Lm]: /
Voltage [V]: -
Number of optical assemblies: 1

Optical assembly Characteristics Type 1

Light Output Ratio (L.O.R.) [%]: 80
Lamp code: LED
ZVEI Code: LED
Nominal power [W]: 26
Nominal luminous [Lm]: 4300
Lamp maximum intensity [cd]: /
Beam angle [°]: /

Number of lamps for optical assembly: 1
Socket: /
Ballast losses [W]: 4.4
Colour temperature [K]: 3000
CRI: 80
Wavelength [Nm]: /
MacAdam Step: 3



Imax=1678 cd C0-180

90° 180° 90°

1500

0°

CIE
nL 0.80
61-88-97-100-80
UGR 18.3-17.2

DIN
A.51

UTE
0.80C+0.00T
F"1=609
F"1+F"2=878
F"1+F"2+F"3=972

CIBSE
BZ3

	R	77	75	73	71	55	53	33	00	DDR
K0.8	58	50	45	41	49	45	44	39	49	
1.0	63	56	51	47	55	50	50	45	56	
1.5	70	65	60	57	63	60	59	54	68	
2.0	74	70	66	64	68	65	64	60	76	
2.5	77	73	70	68	72	69	68	64	80	
3.0	78	76	73	71	74	72	71	67	84	
4.0	80	78	76	74	76	75	73	70	88	
5.0	82	80	78	76	78	76	75	72	90	

QC	A	G	1.15	2000	1000	500		<300	
B			1.50		2000	1000	750	500	<300
C			1.85			2000		1000	500

85°
75°
65°
55°
45°

10² 2 3 4 5 6 8 10³ 2 3 4 5 6 8 10⁴ cd/m²

C0-180 C90-270

UGR diagram

Corrected UGR values (at 4300 lm bare lamp luminous flux)												
Reflect.: ceiling/cav walls work pl. Room dim x y		0.70	0.70	0.50	0.50	0.30	0.70	0.70	0.50	0.50	0.30	0.30
		0.50	0.30	0.50	0.30	0.30	0.50	0.30	0.50	0.30	0.30	0.30
		0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20
		viewed crosswise					viewed endwise					
2H	2H	15.7	16.7	16.0	17.0	17.2	15.1	16.1	15.4	16.3	16.6	16.6
	3H	16.5	17.4	16.9	17.7	18.0	15.4	16.3	15.8	16.6	16.9	16.9
	4H	16.9	17.8	17.3	18.1	18.4	15.5	16.3	15.8	16.6	17.0	17.0
	6H	17.3	18.1	17.7	18.4	18.7	15.5	16.3	15.9	16.6	16.9	16.9
	8H	17.4	18.2	17.8	18.5	18.9	15.5	16.2	15.9	16.6	16.9	16.9
	12H	17.5	18.3	17.9	18.6	19.0	15.5	16.2	15.9	16.5	16.9	16.9
4H	2H	16.0	16.8	16.3	17.1	17.5	16.3	17.1	16.6	17.4	17.8	17.8
	3H	17.0	17.7	17.4	18.1	18.4	16.8	17.5	17.2	17.9	18.3	18.3
	4H	17.5	18.2	17.9	18.5	18.9	17.0	17.6	17.4	18.0	18.4	18.4
	6H	18.1	18.6	18.5	19.0	19.5	17.1	17.7	17.6	18.1	18.5	18.5
	8H	18.3	18.8	18.7	19.2	19.7	17.2	17.7	17.6	18.1	18.5	18.5
	12H	18.4	18.9	18.9	19.3	19.8	17.2	17.7	17.6	18.1	18.6	18.6
8H	4H	17.7	18.2	18.1	18.6	19.0	17.6	18.1	18.1	18.6	19.0	19.0
	6H	18.4	18.8	18.8	19.2	19.7	17.9	18.3	18.4	18.8	19.3	19.3
	8H	18.7	19.0	19.2	19.5	20.0	18.0	18.4	18.5	18.9	19.4	19.4
	12H	18.9	19.3	19.4	19.7	20.3	18.1	18.5	18.6	18.9	19.5	19.5
12H	4H	17.7	18.1	18.1	18.6	19.0	17.7	18.2	18.2	18.6	19.1	19.1
	6H	18.4	18.8	18.9	19.2	19.7	18.1	18.4	18.5	18.9	19.4	19.4
	8H	18.8	19.1	19.3	19.6	20.1	18.2	18.6	18.7	19.0	19.6	19.6
Variations with the observer position at spacing:												
S =		1.0H	0.2 / -0.3		0.2 / -0.3							
		1.5H	0.4 / -0.9		0.4 / -1.0							
		2.0H	1.0 / -1.3		0.9 / -1.3							