


Last information update: May 2018



Ceiling-recessed emergency indication luminaire - LED - Self-Testing

Product code

MU31

Technical description

Luminaire with LED lamp for indicating escape routes. Ceiling-recessed installation. Body frame with white finish, shaped steel, perimeter surface edging. Plastic component holder box. Permanent operation (always on - SA); in event of blackouts guarantees an emergency autonomy of 3 hours with the battery fully charged. Sign visible from a distance of 25m (in compliance with UNI EN 1838). Self-test mode. LED warning lamp with function that indicates which devices are operating correctly and if there are any faults. For explanations of all the operating warning lamp functions, see the instructions sheet. Ni-Cd battery with 24 hour recharge time. Indicator screens available with a separate code (pictogram design L22).

Installation

Ceiling-recessed - by inserting the device into the relative slot using the steel wire spring, compatible with false ceilings between 10 and 30 mm thick.

Dimension (mm)

310x50x82

Colour

White (01)

Mounting

ceiling recessed

Wiring

Inside the structure - the protection panel must be removed and the necessary connections made on the standard terminals.

Notes

Rest Mode function: allows the system to be switched off for short periods. The emergency system must be reactivated using the remote control (code no. MXT0).

Complies with EN60598-1 and pertinent regulations



Product characteristics

Total lighting output [Lm]: 35
 Total power [W]: 1
 Luminous efficacy [Lm/W]: 35.0
 Number of optical assemblies: 1

Total luminous flux at or above an angle of 90° [Lm]: 0
 Emergency luminous flux [Lm]: /
 Voltage [V]: -

Optical assembly Characteristics Type 1

Light Output Ratio (L.O.R.) [%]: /
 Lamp code: /
 ZVEI Code: LED
 Nominal power [W]: 1
 Nominal luminous [Lm]: 35
 Lamp maximum intensity [cd]: /
 Beam angle [°]: /

Number of lamps for optical assembly: 1
 Socket: /
 Ballast losses [W]: /
 Colour temperature [K]: 4000
 CRI: 80
 Wavelength [Nm]: /
 MacAdam Step: /