


Last information update: May 2018



**Ceiling-mounted emergency indication luminaire - LED - Centralized Testing**

**Product code**  
MU34

**Technical description**

Luminaire with LED lamp for indicating escape routes. Ceiling-mounted. White finish, shaped sheet steel component holder structure. Permanent operation (always on - SA); in event of blackouts guarantees an emergency autonomy of 3 hours with the battery fully charged. Sign visible from a distance of 25m (in compliance with UNI EN 1838). Luminaires with centralized testing are equipped with an interface circuit that can interact with the external accessory control unit (code no. MXS9). In the event of a fault or malfunctioning the devices involved are indicated on the control unit display by means of a specific identification number. LED warning lamp with function that indicates which devices are operating correctly and if there are any faults. For explanations of all the operating warning lamp functions, see the instructions sheet. Ni-Cd battery with 24 hour recharge time. Indicator screens available with a separate code (pictogram design L22).

**Installation**

Ceiling-mounted - by removing the cover safety guard and fixing the structure to the surface using screws and screw anchors (not supplied).

**Dimension (mm)**

305x50x95

**Colour**

White (01)

**Mounting**

ceiling surface

**Wiring**

Inside the structure - the protection panel must be removed and the necessary connections made on the standard terminals.

**Notes**

Inhibition Mode Function (only for versions with centralized testing): allows the system to be switched off even for long periods. The emergency system must be reactivated using the control unit code no. MXS9.

Complies with EN60598-1 and pertinent regulations



**Product characteristics**

Total lighting output [Lm]: 35  
Total power [W]: 1  
Luminous efficacy [Lm/W]: 35.0  
Number of optical assemblies: 1

Total luminous flux at or above an angle of 90° [Lm]: 0  
Emergency luminous flux [Lm]: /  
Voltage [V]: -

**Optical assembly Characteristics Type 1**

Light Output Ratio (L.O.R.) [%]: /  
Lamp code: /  
ZVEI Code: LED  
Nominal power [W]: 1  
Nominal luminous [Lm]: 35  
Lamp maximum intensity [cd]: /  
Beam angle [°]: /

Number of lamps for optical assembly: 1  
Socket: /  
Ballast losses [W]: /  
Colour temperature [K]: 4000  
CRI: 80  
Wavelength [Nm]: /  
MacAdam Step: /