

Last information update: May 2018

**large body - warm white - up light wall washer optic****Product code**
N993**Technical description**

Indoor, indirect light, wall-mounted luminaire designed to use warm white PCB LED lamps (3000K). 100% up light beam. The product's optical assembly is made of die-cast aluminium. Product complete with super pure anodized aluminium reflector to guarantee wall washer up light distribution for general lighting. Electronic ballast integrated in the body. Passive heat dissipation.

Installation
Wall-mounted**Dimension (mm)**
178x210x67**Colour**
Black/White (47)**Weight (Kg)**
2.3**Mounting**
wall arm|wall surface**Wiring**
Product complete with electronic components

Complies with EN60598-1 and pertinent regulations

IP20 IP40 for optical assembly

**Product configuration: N993****Product characteristics**


Total lighting output [Lm]: 2880
Total power [W]: 48.1
Luminous efficacy [Lm/W]: 59.9
Life Time: 50,000h - L80 - B10 (Ta 25°C)

Total luminous flux at or above an angle of 90° [Lm]: 2880
Emergency luminous flux [Lm]: /
Voltage [V]: -
Number of optical assemblies: 1

Optical assembly Characteristics Type 1

Light Output Ratio (L.O.R.) [%]: 80
Lamp code: LED
ZVEI Code: LED
Nominal power [W]: 43
Nominal luminous [Lm]: 3600
Lamp maximum intensity [cd]: /
Beam angle [°]: /

Number of lamps for optical assembly: 1
Socket: /
Ballast losses [W]: 5.1
Colour temperature [K]: 3000
CRI: 80
Wavelength [Nm]: /
MacAdam Step: 2



Polar

