



Last information update: May 2018

**600x600 - Neutral White - general light - DALI****Product code**

P017

Technical description

Recessed direct emission luminaire designed to use Neutral White colour 4000K LEDs and be installed in 600x600 modular false ceilings or in plasterboard using a frame to be ordered as an accessory. The optical assembly is made of a thermoplastic material with a satin methacrylate diffuser screen for general light emission. Product complete with DALI components.

Installation

Recessed for installation in 600x600 modular false ceilings or in plasterboard using a frame to be ordered as an accessory.

Dimension (mm)

600x600

Colour

White (01)

Weight (Kg)

2.56

Mounting

ceiling recessed|wall surface

Wiring

product complete with DALI components.

Complies with EN60598-1 and pertinent regulations

**Product configuration: P017****Product characteristics**

Total lighting output [Lm]: 3519.6
 Total power [W]: 32.4
 Luminous efficacy [Lm/W]: 108.6
 Life Time: 50,000h - L80 - B10 (Ta 25°C)


Total luminous flux at or above an angle of 90° [Lm]: 0
 Emergency luminous flux [Lm]: /
 Voltage [V]: -
 Number of optical assemblies: 1

Optical assembly Characteristics Type 1

Light Output Ratio (L.O.R.) [%]: 80
 Lamp code: LED
 ZVEI Code: LED
 Nominal power [W]: 27
 Nominal luminous [Lm]: 4400
 Lamp maximum intensity [cd]: /
 Beam angle [°]: /

Number of lamps for optical assembly: 1
 Socket: /
 Ballast losses [W]: 5.4
 Colour temperature [K]: 4000
 CRI: 80
 Wavelength [Nm]: /
 MacAdam Step: 3


Polar



Utilisation factors

R	77	75	73	71	55	53	33	00	DRR
K0.8	52	44	38	33	42	37	36	31	39
1.0	58	50	44	39	48	43	42	37	46
1.5	66	59	54	50	58	53	52	47	59
2.0	71	65	61	57	64	60	59	54	68
2.5	74	69	66	62	68	64	63	59	73
3.0	76	72	69	66	70	68	66	62	78
4.0	79	75	73	70	74	71	70	66	83
5.0	80	77	75	73	76	74	72	69	86

Luminance curve limit



UGR diagram

Corrected UGR values (at 4400 lm bare lamp luminous flux)											
Reflect.:											
ceiling/cav		0.70	0.70	0.50	0.50	0.30	0.70	0.70	0.50	0.50	0.30
walls		0.50	0.30	0.50	0.30	0.30	0.50	0.30	0.50	0.30	0.30
work pl.		0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20
Room dim		viewed					viewed				
x	y	crosswise					endwise				
2H	2H	17.5	18.7	17.8	19.0	19.3	17.5	18.7	17.8	19.0	19.3
	3H	19.1	20.2	19.4	20.5	20.8	18.0	19.1	18.3	19.4	19.7
	4H	19.7	20.8	20.1	21.1	21.4	18.2	19.2	18.5	19.5	19.9
	6H	20.2	21.2	20.6	21.5	21.9	18.3	19.2	18.6	19.6	19.9
	8H	20.4	21.3	20.8	21.6	22.0	18.3	19.2	18.7	19.5	19.9
	12H	20.5	21.4	20.9	21.7	22.1	18.3	19.1	18.6	19.5	19.9
4H	2H	18.2	19.2	18.5	19.5	19.9	19.7	20.8	20.1	21.1	21.4
	3H	20.0	20.9	20.4	21.2	21.6	20.4	21.3	20.8	21.6	22.0
	4H	20.7	21.5	21.1	21.9	22.3	20.7	21.5	21.1	21.9	22.3
	6H	21.3	22.0	21.8	22.4	22.9	20.9	21.6	21.4	22.0	22.5
	8H	21.5	22.2	22.0	22.6	23.0	21.0	21.6	21.5	22.1	22.5
	12H	21.7	22.3	22.1	22.7	23.2	21.0	21.6	21.5	22.0	22.5
8H	4H	21.0	21.6	21.5	22.1	22.5	21.5	22.2	22.0	22.6	23.0
	6H	21.8	22.3	22.2	22.8	23.2	21.9	22.4	22.4	22.9	23.4
	8H	22.1	22.5	22.5	23.0	23.5	22.1	22.5	22.5	23.0	23.5
	12H	22.3	22.7	22.8	23.2	23.7	22.2	22.6	22.7	23.0	23.6
12H	4H	21.0	21.6	21.5	22.0	22.5	21.7	22.3	22.1	22.7	23.2
	6H	21.8	22.3	22.3	22.8	23.3	22.1	22.5	22.6	23.0	23.5
	8H	22.2	22.6	22.7	23.0	23.6	22.3	22.7	22.8	23.2	23.7
Variations with the observer position at spacing:											
S =	1.0H	0.1 / -0.1		0.1 / -0.1							
	1.5H	0.2 / -0.3		0.2 / -0.3							
	2.0H	0.4 / -0.5		0.4 / -0.5							