


Last information update: June 2018



Large body spotlight - Neutral white - DALI ballast - wide flood optic

Product code
P264

Technical description

Adjustable spotlight with adapter for installation on mains electrified track for high output LED lamp with monochrome emission in a neutral white (4000K) colour. DALI ballast. The luminaire is made of die-cast aluminium and thermoplastic material, allowing 360° rotation about the vertical axis and 90° tilting relative to the horizontal plane. The luminaire has mechanical aiming locks and graduated scales for both movements, operated using the same tool on two screws, one on the optic compartment and one on the adapter for the track. Spotlight equipped with accessory holding ring designed to contain a flat accessory. Another external component can also be applied, selected from directional flaps and an asymmetric screen. All external accessories rotate 360° about the spotlight longitudinal axis.

Installation

On an electrified track

Dimension (mm)
Ø162x314

Colour

White (01) | Grey/Black (74)

Weight (Kg)

2.25

Mounting

three circuit track

Wiring

The DALI components are housed in the luminaire.

Complies with EN60598-1 and pertinent regulations



Product configuration: P264

Product characteristics

Total lighting output [Lm]: 3845
Total power [W]: 35.2
Luminous efficacy [Lm/W]: 109.2
Life Time: > 50,000h - L80 - B10 (Ta 25°C)


Total luminous flux at or above an angle of 90° [Lm]: 0
Emergency luminous flux [Lm]: /
Voltage [V]: -
Number of optical assemblies: 1

Optical assembly Characteristics Type 1

Light Output Ratio (L.O.R.) [%]: 77
Lamp code: LED
ZVEI Code: LED
Nominal power [W]: 32
Nominal luminous [Lm]: 5000
Lamp maximum intensity [cd]: /
Beam angle [°]: 44°

Number of lamps for optical assembly: 1
Socket: /
Ballast losses [W]: 3.2
Colour temperature [K]: 4000
CRI: 80
Wavelength [Nm]: /
MacAdam Step: 2


Polar



Utilisation factors

R	77	75	73	71	55	53	33	00	DRR
K0.8	69	65	63	61	65	63	62	60	78
1.0	72	69	67	65	68	66	66	63	82
1.5	76	73	71	70	72	71	70	68	88
2.0	78	76	75	74	75	74	73	71	93
2.5	80	78	77	76	77	76	75	73	95
3.0	81	80	79	78	78	78	77	75	97
4.0	82	81	80	80	80	79	78	76	99
5.0	82	82	81	81	80	80	79	77	100

Luminance curve limit



UGR diagram

Corrected UGR values (at 5000 lm bare lamp luminous flux)										
Reflect.:										
ceiling	0.70	0.70	0.50	0.50	0.30	0.70	0.70	0.50	0.50	0.30
walls	0.50	0.30	0.50	0.30	0.30	0.50	0.30	0.50	0.30	0.30
work pl.	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20
Room dim										
x										
y										
			viewed					viewed		
			crosswise					endwise		
2H	2H	10.3	10.9	10.6	11.1	11.4	10.3	10.9	10.6	11.1
	3H	10.2	10.7	10.5	11.0	11.3	10.2	10.7	10.5	11.0
	4H	10.1	10.6	10.5	10.9	11.2	10.1	10.6	10.5	10.9
	6H	10.1	10.5	10.4	10.8	11.2	10.1	10.5	10.4	10.8
	8H	10.0	10.5	10.4	10.8	11.1	10.0	10.5	10.4	10.8
	12H	10.0	10.4	10.4	10.8	11.1	10.0	10.4	10.4	10.7
4H	2H	10.1	10.6	10.5	10.9	11.2	10.1	10.6	10.5	10.9
	3H	10.0	10.4	10.4	10.8	11.1	10.0	10.4	10.4	10.8
	4H	9.9	10.3	10.3	10.7	11.1	9.9	10.3	10.3	10.7
	6H	9.9	10.2	10.3	10.6	11.0	9.9	10.2	10.3	10.6
	8H	9.8	10.1	10.3	10.5	11.0	9.8	10.1	10.2	10.5
	12H	9.8	10.0	10.2	10.5	10.9	9.8	10.0	10.2	10.5
8H	4H	9.8	10.1	10.2	10.5	11.0	9.8	10.1	10.3	10.5
	6H	9.7	10.0	10.2	10.4	10.9	9.7	10.0	10.2	10.4
	8H	9.7	9.9	10.2	10.4	10.9	9.7	9.9	10.2	10.4
	12H	9.6	9.8	10.1	10.3	10.8	9.6	9.8	10.1	10.3
12H	4H	9.8	10.0	10.2	10.5	10.9	9.8	10.0	10.2	10.5
	6H	9.7	9.9	10.2	10.3	10.8	9.7	9.9	10.2	10.4
	8H	9.6	9.8	10.1	10.3	10.8	9.6	9.8	10.1	10.3
Variations with the observer position at spacing:										
S =	1.0H		5.4	/	-8.9		5.4	/	-8.9	
	1.5H		8.1	/	-11.2		8.1	/	-11.2	
	2.0H		10.1	/	-12.7		10.1	/	-12.7	