

Laser Pinhole

Design iGuzzini

iGuzzini

Last information update: May 2018



multiple adjustable recessed WW

Product code
P432

Technical description

Two-compartment multiple adjustable luminaire designed for housing 2700K Warm White COB LED light sources with high colour rendering and OPTIBEAM reflector made of thermoplastic material. Rim made of white-coated die-cast aluminium incorporating a black-coated thermoplastic component for guaranteeing maximum visual comfort and preventing stray light dispersion. Flood optic. Adjustable internally around the horizontal axis by 35° and around the vertical axis by 358°. The optical compartments can be adjusted individually. Passive cooling system, by means of a black-coated heat sink made of extruded aluminium. The power supply unit is available with a separate code.

Installation

Recessed installation in false ceilings with 1 mm to 20 mm thickness with steel springs.

Dimension (mm)
164x85x101

Colour
White (01)

Mounting
ceiling surface

Wiring

Constant-current ballasts available with separate code: ON-OFF / 1-10 V dimmable / phase-cut dimmer / the recessed luminaire is supplied with the cable and connector to be connected to the connector provided on the driver.

Complies with EN60598-1 and pertinent regulations



IP20



Product configuration: P432

Product characteristics

Total lighting output [Lm]: 940
Total power [W]: 20
Luminous efficacy [Lm/W]: 47
Life Time: > 50,000h - L80 - B10 (Ta 25°C)


Total luminous flux at or above an angle of 90° [Lm]: 0
Emergency luminous flux [Lm]: /
Voltage [V]: -
Number of optical assemblies: 2

Optical assembly Characteristics Type 1

Light Output Ratio (L.O.R.) [%]: 41
Lamp code: LED
ZVEI Code: LED
Nominal power [W]: 10
Nominal luminous [Lm]: 1150
Lamp maximum intensity [cd]: /
Beam angle [°]: 26°

Number of lamps for optical assembly: 1
Socket: /
Ballast losses [W]: 0
Colour temperature [K]: 2700
CRI: 90
Wavelength [Nm]: /
MacAdam Step: 2


Polar



Utilisation factors

R	77	75	73	71	55	53	33	00	DRR
K0.8	37	35	33	32	34	33	33	32	78
1.0	38	37	35	34	36	35	35	34	82
1.5	40	39	38	37	39	38	37	36	88
2.0	42	41	40	39	40	39	39	38	93
2.5	42	42	41	41	41	41	40	39	95
3.0	43	42	42	42	42	41	41	40	97
4.0	43	43	43	42	42	42	41	41	99
5.0	44	43	43	43	43	43	42	41	100

Luminance curve limit



UGR diagram

Corrected UGR values (at 1150 lm bare lamp luminous flux)											
Reflect.:											
ceiling	walls	0.70	0.70	0.50	0.50	0.30	0.70	0.70	0.50	0.50	0.30
work pl.		0.50	0.30	0.50	0.30	0.30	0.50	0.30	0.50	0.30	0.30
Room dim		0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20
x	y	viewed crosswise					viewed endwise				
2H	2H	2.3	4.4	2.7	4.8	5.1	2.3	4.4	2.7	4.8	5.1
	3H	2.6	4.2	2.9	4.5	4.9	2.5	4.1	2.8	4.4	4.8
	4H	2.6	3.9	3.0	4.3	4.6	2.5	3.8	2.9	4.2	4.5
	6H	2.7	3.6	3.0	3.9	4.3	2.5	3.5	2.9	3.8	4.1
	8H	2.7	3.6	3.0	3.9	4.3	2.5	3.4	2.9	3.7	4.1
	12H	2.7	3.6	3.1	3.9	4.3	2.4	3.3	2.8	3.7	4.1
4H	2H	2.5	3.8	2.9	4.2	4.5	2.6	3.9	3.0	4.3	4.6
	3H	2.9	3.8	3.3	4.2	4.5	2.9	3.8	3.3	4.2	4.5
	4H	2.9	3.8	3.3	4.2	4.6	2.9	3.8	3.3	4.2	4.6
	6H	2.6	4.3	3.1	4.7	5.2	2.6	4.3	3.0	4.7	5.2
	8H	2.5	4.5	3.0	4.9	5.4	2.4	4.4	2.9	4.8	5.3
	12H	2.5	4.5	3.0	5.0	5.5	2.3	4.3	2.8	4.8	5.3
8H	4H	2.4	4.4	2.9	4.8	5.3	2.5	4.5	3.0	4.9	5.4
	6H	2.5	4.3	3.0	4.8	5.3	2.5	4.3	3.0	4.8	5.4
	8H	2.6	4.2	3.1	4.7	5.2	2.6	4.2	3.1	4.7	5.2
	12H	2.8	3.9	3.3	4.4	5.0	2.7	3.9	3.2	4.4	4.9
12H	4H	2.3	4.3	2.8	4.8	5.3	2.5	4.5	3.0	5.0	5.5
	6H	2.5	4.1	3.0	4.6	5.1	2.6	4.2	3.1	4.7	5.3
	8H	2.7	3.9	3.2	4.4	4.9	2.8	3.9	3.3	4.4	5.0
Variations with the observer position at spacing:											
S =	1.0H	0.8 / -0.8					0.8 / -0.8				
	1.5H	1.8 / -2.1					1.8 / -2.1				
	2.0H	3.1 / -3.4					3.1 / -3.4				