

Last information update: May 2018



Fixed circular recessed luminaire - Ø212 mm - warm white - wide flood optic - UGR<10

Product code
P533

Technical description

Fixed round luminaire designed to use a LED lamp with C.O.B. technology. Version with rim for surface-mounting. Optic with supercomfort reflector vacuum-metallised with aluminium vapours and an anti-scratch protective layer. Die-cast aluminium body and passive dissipation system. Product complete with LED lamp in warm white colour tone CRI 90 (3000K). General light emission, with controlled luminance UGR<10 1500 cd/m² α>65° wide flood optic.

Installation

Recessed using torsion springs which allow easy installation in false ceilings with thicknesses ranging from 1 mm to 20 mm.

Dimension (mm)

Ø226x150

Colour

White/Aluminium (39)

Weight (Kg)

2

Mounting

ceiling recessed

Wiring

product complete with DALI components

Complies with EN60598-1 and pertinent regulations



Product configuration: P533

Product characteristics

Total lighting output [Lm]: 4794.6
Total power [W]: 57.8
Luminous efficacy [Lm/W]: 83
Life Time: 50,000h - L80 - B10 (Ta 25°C)


Total luminous flux at or above an angle of 90° [Lm]: 0
Emergency luminous flux [Lm]: /
Voltage [V]: -
Number of optical assemblies: 1

Optical assembly Characteristics Type 1

Light Output Ratio (L.O.R.) [%]: 80
Lamp code: LED
ZVEI Code: LED
Nominal power [W]: 52
Nominal luminous [Lm]: 6000
Lamp maximum intensity [cd]: /
Beam angle [°]: 48°

Number of lamps for optical assembly: 1
Socket: /
Ballast losses [W]: 5.8
Colour temperature [K]: 3000
CRI: 90
Wavelength [Nm]: /
MacAdam Step: 2


Polar



Utilisation factors

R	77	75	73	71	55	53	33	00	DRR
K0.8	72	68	66	64	68	65	65	62	78
1.0	75	72	69	68	71	69	68	66	82
1.5	79	76	74	73	75	74	73	71	88
2.0	81	80	78	77	78	77	76	74	93
2.5	83	81	80	79	80	79	78	76	96
3.0	84	83	82	81	82	81	80	78	98
4.0	85	84	84	83	83	82	81	79	99
5.0	85	85	84	84	84	83	82	80	100

Luminance curve limit



UGR diagram

Corrected UGR values (at 6000 lm bare lamp luminous flux)											
Reflect.:		viewed crosswise					viewed endwise				
ceiling	cav	0.70	0.70	0.50	0.50	0.30	0.70	0.70	0.50	0.50	0.30
walls		0.50	0.30	0.50	0.30	0.30	0.50	0.30	0.50	0.30	0.30
work pl.		0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20
Room dim		viewed crosswise					viewed endwise				
x	y										
2H	2H	4.4	5.0	4.7	5.2	5.5	4.4	5.0	4.7	5.2	5.5
	3H	4.4	4.9	4.7	5.2	5.5	4.3	4.9	4.7	5.1	5.4
	4H	4.3	4.8	4.7	5.1	5.4	4.3	4.8	4.6	5.1	5.4
	6H	4.3	4.7	4.6	5.0	5.4	4.2	4.7	4.6	5.0	5.3
	8H	4.2	4.7	4.6	5.0	5.3	4.2	4.6	4.5	5.0	5.3
	12H	4.2	4.6	4.6	5.0	5.3	4.1	4.6	4.5	4.9	5.3
4H	2H	4.3	4.8	4.6	5.1	5.4	4.3	4.8	4.7	5.1	5.4
	3H	4.3	4.7	4.7	5.0	5.4	4.3	4.7	4.7	5.1	5.4
	4H	4.2	4.6	4.6	5.0	5.4	4.2	4.6	4.6	5.0	5.4
	6H	4.2	4.5	4.6	4.9	5.3	4.2	4.5	4.6	4.9	5.3
	8H	4.1	4.4	4.6	4.8	5.3	4.1	4.4	4.6	4.8	5.3
	12H	4.1	4.3	4.5	4.8	5.2	4.1	4.3	4.5	4.8	5.2
8H	4H	4.1	4.4	4.6	4.8	5.3	4.1	4.4	4.6	4.8	5.3
	6H	4.0	4.3	4.5	4.7	5.2	4.0	4.3	4.5	4.7	5.2
	8H	4.0	4.2	4.5	4.7	5.2	4.0	4.2	4.5	4.7	5.2
	12H	3.9	4.1	4.4	4.6	5.1	3.9	4.1	4.4	4.6	5.1
12H	4H	4.1	4.3	4.5	4.8	5.2	4.1	4.3	4.5	4.8	5.2
	6H	4.0	4.2	4.5	4.7	5.2	4.0	4.2	4.5	4.7	5.2
	8H	3.9	4.1	4.4	4.6	5.1	3.9	4.1	4.4	4.6	5.1
Variations with the observer position at spacing:											
S =	1.0H	5.8 / -5.9					5.8 / -5.9				
	1.5H	8.5 / -7.1					8.5 / -7.1				
	2.0H	10.5 / -8.0					10.5 / -8.0				