

Last information update: June 2018

**spotlight - warm white medium optic****Product code**

P683

**Technical description**

Adjustable spotlight with adapter for installation on mains voltage track for LED source with CoB technology, Warm White (3000K) emission. Electronic control gear housed inside the track-mounted power supply box. The luminaire is made of die-cast aluminium and thermoplastic. OPTI BEAM superpure aluminium reflector with high luminous efficacy and uniform distribution, medium optic. Features 90° inclination on the horizontal plane and 360° rotation around the vertical axis, with mechanical locking device for aiming. Passive cooling system. Possibility of installing a refractor, to be ordered separately, for elliptical light beam distribution.

**Installation**

The luminaire can be installed on a standard electrified track or on an appropriate channel incorporating an electrified track.

**Dimension (mm)**

Ø120x197

**Colour**

White (01) | Black (04)

**Weight (Kg)**

1.82

**Mounting**

three circuit track|ceiling surface

**Wiring**

product inclusive of electronic components incorporated into the track-mounted box.

Complies with EN60598-1 and pertinent regulations

IP20 IP40 for optical assembly

**Product configuration: P683****Product characteristics**


Total lighting output [Lm]: 3450  
Total power [W]: 36.8  
Luminous efficacy [Lm/W]: 93.8  
Life Time: > 50,000h - L80 - B10 (Ta 25°C)

Total luminous flux at or above an angle of 90° [Lm]: 0  
Emergency luminous flux [Lm]: /  
Voltage [V]: -  
Number of optical assemblies: 1

**Optical assembly Characteristics Type 1**

Light Output Ratio (L.O.R.) [%]: 69  
Lamp code: LED  
ZVEI Code: LED  
Nominal power [W]: 33  
Nominal luminous [Lm]: 5000  
Lamp maximum intensity [cd]: /  
Beam angle [°]: 20°

Number of lamps for optical assembly: 1  
Socket: /  
Ballast losses [W]: 3.8  
Colour temperature [K]: 3000  
CRI: 80  
Wavelength [Nm]: /  
MacAdam Step: 2



**Polar**

