


Last information update: May 2018



**Minimal 2-compartment recessed luminaire - Neutral White LED - Wall Washer - DALI**

**Product code**


P974

**Technical description**

2-compartment recessed luminaire with wall washer fixed optic for warm white LED with high colour rendering index. Passive cooling system. Luminaire body with die-cast radiant aluminium surface, for flush installation on ceilings (frameless). Adapter for false ceilings with bracket system adapting to panel thickness, for installation flush with the ceiling. Special optical systems for defined light distribution on the wall with no shadow areas. The position next to the asymmetrical units ensures a considerable reduction in direct glare, without compromising the quality of light emitted. Reflectors - flow recuperators in superpure aluminium, diffusers - PMMA refractors, thermoplastic containment structures. Supplied with DALI dimmable power supply unit connected to the luminaire.

**Installation**

Recessed with anti-fall steel wire springs on a specific adapter (included), ensuring flush installation on ceiling. Fixed to false ceiling with adapter screws (thickness from 12.5 mm to 25 mm); the wall is then filled and skim-coated; insertion of recess and finishing touches. Recess opening 74 x 143 mm. To ensure proper lighting of walls, check distances and centre to centre distances on the instructions sheet.



**Dimension (mm)**

141x72x109

**Colour**

White (01) | Black (04)

**Weight (Kg)**

0.96

**Mounting**

wall recessed|ceiling recessed

**Wiring**

Quick-fit power supply connection to terminal block - Digital electronic wiring enables dimming with DALI or TOUCH DIM systems.

Complies with EN60598-1 and pertinent regulations

IP20 IP43 On the visible part of the product once installed



**Product configuration: P974.01**

**Product characteristics**

Total lighting output [Lm]: 1271.8  
 Total power [W]: 21.2  
 Luminous efficacy [Lm/W]: 60  
 Life Time: 50,000h - L80 - B10 (Ta 25°C)


Total luminous flux at or above an angle of 90° [Lm]: 0  
 Emergency luminous flux [Lm]: /  
 Voltage [V]: 230  
 Number of optical assemblies: 1

**Optical assembly Characteristics Type 1**

Light Output Ratio (L.O.R.) [%]: 53  
 Lamp code: LED  
 ZVEI Code: LED  
 Nominal power [W]: 17  
 Nominal luminous [Lm]: 2400  
 Lamp maximum intensity [cd]: /  
 Beam angle [°]: /

Number of lamps for optical assembly: 1  
 Socket: /  
 Ballast losses [W]: 4.2  
 Colour temperature [K]: 4000  
 CRI: 80  
 Wavelength [Nm]: /  
 MacAdam Step: 3

Polar



Illuminances

Lux Wall distance = 1m

3						●					
	0.5	1	3	9	27	79	85	41	16	6	2
2	1	3	6	16	47	79	79	55	31	16	8
	2	3	8	17	33	55	63	47	29	17	10
1	2	4	7	13	24	40	47	38	25	16	10
	2	4	6	10	17	27	32	28	21	14	9
0											
	m	-2	-1	0	1	2	3				